

# Liquid Tight


Steel & Malleable Iron



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
54403	3/8"	25	100	29
54413	1/2"	25	100	29
54423	3/4"	25	100	42
54433	1 "	-	10	66
54443	1-1/4"	-	10	90
54453	1-1/2"	-	5	113
54463	2"	-	5	180
54468	2-1/2 "	-	1	587

## NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C	Thread Spec NPT
1/2"	1.03	1.38	0.531	14
3/4"	1.06	1.25	0.563	14
1"	1.19	1.66	0.594	14
1-1/4"	1.41	1.66	0.625	11-1/2
1-1/2"	1.50	1.81	0.719	11-1/2
2"	1.56	2.00	0.734	11-1/2
2-1/2"	1.75	2.38	0.766	11-1/2



## Liquid Tight Connectors

**TYPE:** 45°, Insulated with Ground Lug

**MATERIAL:** Steel & Malleable Iron

**FINISH:** Zinc Electro Plated

### APPLICATIONS:

- Used to connect flexible metallic liquid tight conduit and Type B flexible non-metallic conduit to a box or enclosure
- For indoor or outdoor locations

### FEATURES:

- Liquid tight-water and oil
- Tapered NPT, male hub
- Includes sealing washer & locknut
- Sizes 3/8"-2" Steel
- Sizes 2-1/2"-4" Malleable
- With insulated Throat Liner

### COMPLIANCE:



File No.:  
E244047



Electrical Resource International  
440.878.1199  
[www.electrical-resource.com](http://www.electrical-resource.com)