

SERVICE ENTRANCE


Aluminum



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
88010	1/2"	-	25	52
88020	3/4"	-	25	63
88030	1 "	-	25	46
88040	1-1/4"	-	25	56
88050	1-1/2"	-	10	93
88060	2 "	-	10	160
88065	2-1/2"	-	1	450
88070	3 "	-	1	700
88075	3-1/2"	-	1	650
88080	4 "	-	1	650

NOMINAL DIMENSIONS (Inches):

Part No	A	B	C
88010	3.362	2.543	1.996
88020	3.746	2.890	2.244
88030	4.180	3.346	2.523
88040	4.772	3.634	2.968
88050	5.938	4.496	3.456
88060	7.811	5.807	4.543
88065	10.453	6.937	6.141
88070	10.846	7.134	6.188
88075	13.925	8.744	7.900
88080	13.925	8.744	7.893



Electrical Resource International
440.878.1199
www.electrical-resource.com

Entrance Caps

TYPE: Clamp

MATERIAL: Aluminum with Steel Strap

APPLICATIONS:

- Used as a point of connection in an overhead service entrance and can be mounted on threaded or unthreaded Rigid, IMC or EMT conduit

FEATURES:

- Protects wires against sharp edges
- Provides a water resistant cap protecting service entrance conductors, required for overhead applications
- Phenolic Insulator with multiple holes

COMPLIANCE:



File No.:
E248623