

SERVICE ENTRANCE


Aluminum



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
88210	1/2"	-	50	21
88220	3/4"	-	50	26
88230	1 "	-	25	38
88240	1-1/4"	-	20	72
88250	1-1/2"	-	10	72
88260	2 "	-	5	126
88265	2-1/2"	-	2	360
88270	3 "	-	1	600
88275	3-1/2"	-	1	630
88280	4 "	-	1	630
88285	5"	-	1	1230
88290	6"	-	1	1000

NOMINAL DIMENSIONS (Inches):

Part No	A	B	C
88210	2.945	2.346	1.996
88220	3.395	2.504	2.244
88230	3.855	2.972	2.523
88240	4.430	3.358	2.968
88250	5.620	3.972	3.456
88260	7.118	5.106	4.543
88265	10.633	7.142	6.141
88270	10.72	7.181	6.188
88275	13.634	8.799	7.900
88280	13.89	8.850	7.893
88285	12.28	8.77	8.25
88290	12.25	9.76	8.25



Electrical Resource International
440.878.1199
www.electrical-resource.com

Entrance Caps

TYPE: Threaded

MATERIAL: Aluminum

APPLICATIONS:

- Used as a point of connection in an overhead service entrance and can be mounted on Rigid or IMC conduit

FEATURES:

- Protects wires against sharp edges
- Provides a water resistant cap protecting service entrance conductors, required for overhead applications
- Phenolic Insulator with multiple holes

COMPLIANCE:



File No.:
E248623