

Rigid Standard 90° Elbows

Material & Finish:

6063 Aluminum Alloy in Temper Designation T1

Application:

- Used on conduit raceways to interconnect conduit.
- Used on conduit raceways to interconnect conduit runs and other fittings.
- Used to change conduit direction.

Features:

- Corrosion Resistant to most industrial environments.
- Bulk sizes are fitted with color-coded thread protectors.



Part No.	Trade Size		Straight (S)		Min. Radius (R)		Offset (O)		Weight/100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	lb	kg	*Bulk
87210	1/2"	16	2.50	64	4.00	102	6.960	177	22	10	50
87220	3/4"	21	2.50	64	4.50	114	7.730	185	32	15	50
87230	1"	27	3.00	76	5.75	146	9.36	238	62	28	25
87240	1-1/4"	35	3.25	83	7.25	184	11.38	289	99	45	20
87250	1-1/2"	41	3.50	89	8.25	210	12.76	329	137	62	15
87260	2"	53	4.25	108	9.50	241	15.01	381	228	103	10
87265	2-1/2"	63	5.00	127	10.5	267	17.11	435	427	194	108*
87270	3"	78	5.50	140	13.0	330	20.33	516	752	342	70*
87275	3-1/2"	91	6.25	159	15.0	381	23.38	594	889	403	54*
87280	4"	103	7.00	178	16.0	406	25.40	645	1049	475	40*
87285	5"	129	11.0	279	24	610	37.86	784	2125	964	1*
87290	6"	155	12.5	318	30	762	45.99	1168	3738	1696	1*

Available in standard sizes 90°, 60°, 45°, 30°, 225° bends. Dimensions & Weights are Nominal, subject to change without notice.

Compliance: UL 6A, ANSI C80.5

