

Rigid Couplings

Material & Finish:

6063 Aluminum Alloy in Temper Designation T1

Application:

·Used for joining threaded RIGID conduit together.

Features:

·Corrosion Resistant to most industrial environments.



Part No.	Trade Size		Length (A)		Outside Diameter (B)		Threads per in/mm		Weight/ 100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	lb	kg	
87110	1/2"	16	1.63	41.30	1.01	25.7	14.0	356	6	3	100
87120	3/4"	21	1.64	41.70	1.25	31.8	14.0	356	9	4	50
87130	1"	27	1.97	50.00	1.53	38.7	11.5	305	13	6	30
87140	1-1/4"	35	2.03	51.60	1.87	47.5	11.5	305	19	9	25
87150	1-1/2"	41	2.06	52.40	2.16	54.7	11.5	305	23	10	25
87160	2"	53	2.13	54.00	2.65	67.3	11.5	305	35	16	20
87165	2-1/2"	63	3.19	81.00	3.25	82.6	8.0	203	68	31	24
87170	3"	78	3.31	84.10	3.87	98.3	8.0	203	91	41	18
87175	3-1/2"	91	3.41	86.50	4.50	114.3	8.0	203	108	49	12
87180	4"	103	3.52	89.30	4.88	123.8	8.0	203	142	64	10
87185	5"	129	3.95	100.4	6.00	152.4	8.0	203	242	110	1
87190	6"	155	4.25	108.0	7.20	182.9	8.0	203	320	145	1

Dimensions & weights are nominal, subject to change without notice.

Compliance: UL 6A, ANSI C80.5

