

# Hot-Dipped Galvanized Steel

## Rigid Standard 90° Elbows

### Material & Finish:

Hot-Dipped Galvanized Steel

### Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.



### Features:

- Hot-dip galvanized exterior provides anti-corrosion and abrasion.
- Organic Interior Diameter insulating coating promotes smooth surface for easy wire pulling.
- Provides mechanical protection for conductors.
- Bulk sizes are fitted with color-coded thread protectors.

Part No.	Trade Size		Straight (S)		Min. Radius (R)		Offset (O)		Weight/100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	lb	kg	*Bulk
47210	1/2"	16	2.50	64	4.00	102	6.960	177	70	32	50
47220	3/4"	21	2.50	64	4.50	114	7.730	185	112	51	50
47230	1"	27	3.00	76	5.75	146	9.36	238	192	87	25
47240	1-1/4"	35	3.25	83	7.25	184	11.38	289	320	145	20
47250	1-1/2"	41	3.50	89	8.25	210	12.76	329	413	187	15
47260	2"	53	4.25	108	9.50	241	15.01	381	670	304	10
47265	2-1/2"	63	5.00	127	10.5	267	17.11	435	1200	544	108*
47270	3"	78	5.50	140	13.0	330	20.33	516	1900	862	70*
47275	3-1/2"	91	6.25	159	15.0	381	23.38	594	2800	1270	54*
47280	4"	103	7.00	178	16.0	406	25.40	645	3100	1406	40*
47285	5"	129	11.0	279	24	610	37.86	784	6800	3084	1*
47290	6"	155	12.5	318	30	762	45.99	1168	11400	5171	1*

Available in standard sizes 90°, 60°, 45°, 30°, 225° bends. Dimensions & weights are nominal, subject to change without notice.

Compliance: UL 6, ANSI C80.1

File No: E468552

