

RIGID Standard 90° Elbows



Material & Finish:

Stainless Steel, Type 304 or Type 316

Application:

- Used on conduit raceways to interconnect conduit.
- Used on conduit raceways to interconnect conduit runs and other fittings.
- Used to change conduit direction.

Features:

- Corrosion resistant at extreme temperatures to most industrial environments.
- Bulk sizes are fitted with color-coded thread protectors.

Part No.		Trade Size		Straight (S)		Min. Radius (R)		Offset (O)		Weight/100 pcs		Pcs/Ship Carton
304	316	US	Metric	in	mm	in	mm	in	mm	lb	kg	
77210-304	77210-316	1/2"	16	2.50	64	4.00	102	6.96	177	77	35	50
77220-304	77220-316	3/4"	21	2.50	64	4.50	114	7.73	185	110	50	50
77230-304	77230-316	1"	27	3.00	76	5.75	146	9.36	238	198	90	25
77240-304	77240-316	1-1/4"	35	3.25	83	7.25	184	11.38	289	316	143	20
77250-304	77250-316	1-1/2"	41	3.50	89	8.25	210	12.76	329	434	197	15
77260-304	77260-316	2"	53	4.25	108	9.50	241	15.01	381	683	310	10
77265-304	77265-316	2-1/2"	63	5.00	127	10.5	267	17.11	435	1168	530	108*
77270-304	77270-316	3"	78	5.50	140	13.0	330	20.33	516	1791	813	70*
77275-304	77275-316	3-1/2"	91	6.25	159	15.0	381	23.38	594	2646	1200	54*
77280-304	77280-316	4"	103	7.00	178	16.0	406	25.40	645	3169	1438	40*
77285-304	77285-316	5"	129	11.0	279	24.0	610	37.86	784	6850	3107	1*
77290-304	77290-316	6"	155	12.5	318	30.0	762	45.99	1168	10498	4762	1*

Available in standard sizes 90°, 60°, 45°, 30°, 22.5° bend. Dimensions are nominal, subject to change without notice.

Compliance: UL 6A, ANSI C80.5

