

Stainless Steel

Rigid Large Radius 90° Elbows



Material & Finish:

Stainless Steel, Type 304 or Type 316

Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.

Features:

- Corrosion resistant at extreme temperatures to most industrial environments.
- Bulk sizes are fitted with color-coded thread protectors.

Part No.		Trade Size		Straight (S)		Min. Radius (R)		Offset (O)	
304	316	US	Metric	in	mm	in	mm	in	mm
77240/65-12-304	77240/65-12-316	1-2.5"	27-63	9	227	12	305	21	533
77240/70-15-304	77240/70-15-316	1-3"	27-78	9	227	15	381	24	610
77240/80-18-304	77240/80-18-316	1-4"	27-103	10	254	18	457	32	813
77240/80-24-304	77240/80-24-316	1-4"	27-103	11	279	24	610	35	889
77240/90-30-304	77240/90-30-316	1-6"	27-155	11	279	30	762	41	1041
77240/90-36-304	77240/90-36-316	1-6"	27-155	11	279	36	914	47	1194
77240/90-42-304	77240/90-42-316	1-6"	27-155	12	305	42	1067	54	1372
77240/90-48-304	77240/90-48-316	1-6"	27-155	12	305	48	1219	60	1524
77240/90-60-304	77240/90-60-316	1-6"	27-155	12	305	60	1219	72	1829

Available in standard sizes 90°, 60°, 45°, 30°, 22.5° bend. Dimensions are nominal, subject to change without notice.

Compliance: UL 6A, ANSI C80.5

