

Hot-Dipped Galvanized Steel

Electrical Metallic Tubing (EMT)

Material & Finish:

Hot-Dipped Galvanized Steel

Application:

·Used to provide a continuous raceway for wire pulling.

Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- Organic Interior Diameter coating promotes smooth surface for easy wire pulling.
- High grade mild strip steel provides durability and longevity.
- Maintains ductility, providing easy bending, cutting and joining.
- Installed with the use of set screw and compression type couplings and connectors.
- Unthreaded.



Part No.	Trade Size		Dimensions				Weight/ 100 Ft (30.5M)		Qty/ Master Bundle	
			Outside		Wall Thickness		lb	kg	ft	pcs
	US	Metric	in	mm	in	mm				
41710	1/2"	16	0.706	17.93	0.042	1.07	30	14	7000	700
41720	3/4"	21	0.922	23.42	0.049	1.25	46	21	5000	500
41730	1"	27	1.163	29.54	0.057	1.45	67	30	3000	300
41740	1-1/4"	35	1.510	38.35	0.065	1.65	101	45	2000	200
41750	1-1/2"	41	1.740	44.20	0.065	1.65	116	53	1500	150
41760	2"	53	2.197	55.80	0.065	1.65	148	67	1200	120
41765	2-1/2"	63	2.875	73.03	0.072	1.83	216	98	610	61
41770	3"	78	3.500	88.90	0.072	1.83	263	119	510	51
41775	3-1/2"	91	4.000	101.60	0.083	2.11	349	158	370	37
41780	4"	103	4.500	114.30	0.083	2.11	393	178	300	30

Dimensions & weights are nominal, subject to change without notice.

Outside diameter tolerances:

+/- .005 in. (.13mm) for trade sizes 1/2 (16mm) through 2 (53mm);

+/- .010 in. (.25mm) for trade sizes 2-1/2 (63mm);

+/- .015 in. (.38mm) for trade size 3 (78mm);

+/- .020 in. (.51mm) for trade sizes 3-1/2 (91mm) and 4 (103mm).

NOTE: Length = 10 ft. (3.05m) with a tolerance of +/- .25 in. (6.35 mm)

Compliance: UL 797, ANSI C80.3

File No: E322204

