

Hot-Dipped Galvanized Steel

EMT Standard 45° Elbows



Material & Finish:

Hot-Dipped Galvanized Steel

Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.

Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- Organic Interior Diameter coating promotes smooth surface for easy wire pulling.
- Provides mechanical protection for conductors.

Part No.	Trade Size		Straight (S)		Min. Radius (R)		Offset 1 (O1)		Offset 2 (O2)		Weight/100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	in	mm	lb	kg	*Bulk
47510	1/2"	16	1.50	38	4.00	102	6.13	156	2.50	64	18	8	50
47520	3/4"	21	1.50	38	4.50	114	7.38	187	3.13	80	33	15	50
47530	1"	27	1.88	48	5.75	146	8.75	222	3.63	92	56	25	25
47540	1-1/4"	35	2.00	51	7.25	184	10.13	257	4.13	105	97	44	20
47550	1-1/2"	41	2.00	51	8.25	210	13.13	333	5.38	137	145	66	15
47560	2"	53	2.00	51	9.50	241	13.13	333	5.50	140	185	84	10
47565	2-1/2"	63	3.00	76	10.5	267	17.50	445	7.25	184	360	163	286*
47570	3"	78	3.18	81	13.0	330	17.50	445	7.25	184	438	199	132*
47575	3-1/2"	91	3.25	83	15.0	381	26.13	664	10.88	276	873	396	90*
47580	4"	103	3.38	86	16.0	406	26.25	667	10.88	276	983	446	72*

Available in standard sizes 90°, 60°, 45°, 30°, 225° bends. Dimensions & Weights are Nominal, subject to change without notice.

Compliance: UL 797, ANSI C80.3

File No: E322204

