

# Hot-Dipped Galvanized Steel

## EMT Standard 90° Elbows



### Material & Finish:

Hot-Dipped Galvanized Steel

### Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.

### Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- Organic Interior Diameter coating promotes smooth surface for easy wire pulling.
- Provides mechanical protection for conductors.

Part No.	Trade Size		Straight (S)		Min. Radius (R)		Offset (O)		Weight/100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	lb	kg	*Bulk
47410	1/2"	16	2.50	64	4.00	102	6.960	177	26	12	50
47420	3/4"	21	2.50	64	4.50	114	7.730	185	46	21	50
47430	1"	27	3.00	76	5.75	146	9.36	238	92	42	25
47440	1-1/4"	35	3.25	83	7.25	184	11.38	289	135	61	20
47450	1-1/2"	41	3.50	89	8.25	210	12.76	329	200	91	20
47460	2"	53	4.25	108	9.50	241	15.01	381	280	127	10
47465	2-1/2"	63	5.00	127	10.5	267	17.11	435	500	227	156*
47470	3"	78	5.50	140	13.0	330	20.33	516	750	340	88*
47475	3-1/2"	91	6.25	159	15.0	381	23.38	594	1014	460	50*
47480	4"	103	7.00	178	16.0	406	25.40	645	1300	590	40*

Available in standard sizes 90°, 60°, 45°, 30°, 225° bend. Dimensions & weights are nominal, subject to change without notice.

Compliance: UL 797, ANSI C80.3

File No: E322204

