

Hot-Dipped Galvanized Steel

Large Radius 90° Elbows

Material & Finish:

Hot-Dipped Galvanized Steel

Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.

Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- Organic Interior Diameter coating promotes smooth surface for easy wire pulling.
- Provides mechanical protection for conductors.



Part No.		Trade Size		Straight (S)		Min. Radius (R)		Offset (O)	
EMT	RIGID	US	Metric	in	mm	in	mm	in	mm
47440/65-12	47240/65-12	1-2.5"	27-63	9	227	12	305	21	533
47440/70-15	47240/70-15	1-3"	27-78	9	227	15	381	24	610
47440/80-18	47240/80-18	1-4"	27-103	10	254	18	457	32	813
47440/80-24	47240/80-24	1-4"	27-103	11	279	24	610	35	889
47440/80-30	47240/90-30	1-6"	27-155	11	279	30	762	41	1041
47440/80-36	47240/90-36	1-6"	27-155	11	279	36	914	47	1194
47440/80-42	47240/90-42	1-6"	27-155	12	305	42	1067	54	1372
47440/80-48	47240/90-48	1-6"	27-155	12	305	48	1219	60	1524
47440/80-60	47240/90-60	1-6"	27-155	12	305	60	1219	72	1829

Available in standard sizes 90°, 60°, 45°, 30°, 225° bend. Dimensions & Weights are Nominal, subject to change without notice.

Compliance: UL 797 ANSI C80.3, UL 6 ANSI C80.1

File No: E322204, E468552

