

# Hot-Dipped Galvanized Steel

## RIGID Nipples

Quick Reference by Part Number & Size

### Material & Finish:

Hot-Dipped Galvanized Steel

### Application:

- Used to connect two steel outlet boxes or metal enclosures.
- Used to extend a length of threaded Rigid conduit.

### Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- NPT Threads.



TRADE SIZE	O.D.	LENGTH											
		CLOSE	1-1/2"	2"	2-1/2"	3"	3-1/2"	4"	5"	6"	8"	10"	12"
1/2"	0.840	48010	48011	48012	48013	48014	48015	48016	48018	48110	48111	48112	48113
3/4"	1.02	48020	48021	48022	48023	48024	48025	48026	48028	48120	48121	48122	48123
1"	1.32	48030		48032	48033	48034	48035	48036	48038	48130	48131	48132	48133
1-1/4"	1.660	48040		48042	48043	48044	48045	48046	48048	48140	48141	48142	48143
1-1/2"	1.900	48050		48052	48053	48054	48055	48056	48058	48150	48151	48152	48153
2"	2.38	48060			48063	48064	48065	48066	48068	48160	48161	48162	48163
2-1/2"	2.88	49060				49064	49065	49066	49068	49160	49161	49162	49163
3"	3.500	48070				48074	48075	48076	48078	48170	48171	48172	48173
3-1/2"	4.000	49070						49076	49078	49170	49171	49172	49173
4"	4.500	48080						48086	48088	48180	48181	48182	48183
5"	5.56	49280							49288	49380	49381	49382	49383
6"	6.63	48090								48098	48190	48191	48192

Compliance: UL 6, ANSI C80.1

File No: E468552



# Hot-Dipped Galvanized Steel

## RIGID Nipples

Page 1 of 2

### Material & Finish:

Hot-Dipped Galvanized Steel

### Application:

- Used to connect two steel outlet boxes or metal enclosures.
- Used to extend a length of threaded Rigid conduit.



### Features:

- Hot-dip galvanized exterior provides anti-corrosion and abrasion.
- NPT Threads.

Part No.	Length	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt.(lbs)/ 100 pcs
Trade Size 1/2" O.D.: 0.84				
48010	Close	25	250	6
48011	1-1/2"	25	250	8
48012	2"	25	250	12
48013	2-1/2"	25	250	15
48014	3"	25	250	19
48015	3-1/2"	25	150	22
48016	4"	25	150	26
48018	5"	-	25	33
48110	6"	-	25	40
48111	8"	-	25	46
48112	10"	-	25	52
48113	12"	-	25	58
Trade Size 3/4" O.D.: 1.015				
48020	Close	25	250	9
48021	1-1/2"	25	250	9
48022	2"	25	250	14
48023	2-1/2"	25	150	19
48024	3"	25	150	24
48025	3-1/2"	25	150	28
48026	4"	-	25	34
48028	5"	-	25	43
48120	6"	-	25	52
48121	8"	-	25	61
48122	10"	-	25	70
48123	12"	-	25	89

Length Tolerances: +/- 1/16" (1.59mm)

Part No.	Length	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt.(lbs)/ 100 pcs
Trade Size 1" O.D.: 1.315				
48030	Close	25	150	16
48032	2"	25	150	22
48033	2-1/2"	-	25	28
48034	3"	-	25	36
48035	3-1/2"	-	25	43
48036	4"	-	25	49
48038	5"	-	25	64
48130	6"	-	25	78
48131	8"	-	25	88
48132	10"	-	25	97
48133	12"	-	25	106
Trade Size 1-1/4" O.D.: 1.660				
48040	Close	-	25	22
48042	2"	-	25	28
48043	2-1/2"	-	25	37
48044	3"	-	25	47
48045	3-1/2"	-	25	55
48046	4"	-	25	66
48048	5"	-	25	87
48140	6"	-	25	100
48141	8"	-	25	115
48142	10"	-	25	130
48143	12"	-	25	145

Weights are nominal, subject to change without notice.

Compliance: UL 6, ANSI C80.1, File No: E468552



# Hot-Dipped Galvanized Steel

## RIGID Nipples

Page 2 of 2

### Material & Finish:

Hot-Dipped Galvanized Steel

Part No.	Length	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt.(lbs)/ 100 pcs
Trade Size 1-1/2" O.D.: 1.900				
48050	Close	-	25	28
48052	2"	-	25	34
48053	2-1/2"	-	25	44
48054	3"	-	25	56
48055	3-1/2"	-	25	68
48056	4"	-	25	80
48058	5"	-	25	103
48150	6"	-	25	122
48151	8"	-	25	162
48152	10"	-	25	182
48153	12"	-	25	202
Trade Size 2" O.D.: 2.375				
48060	Close	-	25	44
48063	2-1/2"	-	25	59
48064	3"	-	25	72
48065	3-1/2"	-	25	88
48066	4"	-	25	103
48068	5"	-	25	132
48160	6"	-	25	160
48161	8"	-	12	215
48162	10"	-	10	260
48163	12"	-	10	305
Trade Size 2-1/2" O.D.: 2.875				
49060	Close	-	10	84
49064	3"	-	10	100
49065	3-1/2"	-	10	120
49066	4"	-	10	150
49068	5"	-	10	132
49160	6"	-	10	240
49161	8"	-	10	320
49162	10"	-	5	400
49163	12"	-	5	480

Compliance: UL 6, ANSI C801, File No: E468552



Part No.	Length	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt.(lbs)/ 100 pcs
Trade Size 3" O.D.: 3.500				
48070	Close	-	10	118
48074	3"	-	10	125
48075	3-1/2"	-	10	190
48076	4"	-	10	200
48078	5"	-	10	260
48170	6"	-	10	300
48171	8"	-	5	400
48172	10"	-	5	500
48173	12"	-	5	600
Trade Size 3-1/2" O.D.: 4.000				
49070	Close	-	10	160
49076	4"	-	6	240
49078	5"	-	6	320
49170	6"	-	5	373
49171	8"	-	3	490
49172	10"	-	3	610
49173	12"	-	3	730
Trade Size 4" O.D.: 4.500				
48080	Close	-	10	180
48086	4"	-	6	285
48088	5"	-	6	380
48180	6"	-	5	440
48181	8"	-	3	590
48182	10"	-	3	740
48183	12"	-	3	890
Trade Size 5" O.D.: 5.563				
49280	Close	-	1	240
49288	5"	-	1	480
49380	6"	-	1	600
49381	8"	-	1	800
49382	10"	-	1	1000
49383	12"	-	1	1200
Trade Size 6" O.D.: 6.625				
48090	Close	-	1	350
48098	5"	-	1	660
48190	6"	-	1	820
48191	8"	-	1	1120
48192	10"	-	1	1450
48193	12"	-	1	1885

Weights are nominal, subject to change without notice.

Length Tolerances: +/- 1/16" (1.59mm)