

Hot-Dipped Galvanized Steel

Rigid Standard 45° Elbows



Material & Finish:

Hot-Dipped Galvanized Steel

Application:

- Used on conduit raceways to interconnect conduit to change direction.
- Used on conduit raceways to interconnect conduit runs and other fittings.

Features:

- Hot-dip galvanized exterior provides anti-corrosion and anti-abrasion.
- Organic Interior Diameter coating promotes smooth surface for easy wire pulling.
- Bulk sizes are fitted with color-coded thread protectors.

Part No.	Trade Size		Straight (S)		Min. Radius (R)		Offset 1 (O1)		Offset 2 (O2)		Weight/ 100 pcs		Pcs/Ship Carton
	US	Metric	in	mm	in	mm	in	mm	lb	kg	lb	kg	
47310	1/2"	16	1.50	38	4.00	102	7.00	178	2.88	73	55	25	*Bulk
47320	3/4"	21	1.50	38	4.50	114	7.88	200	3.25	83	82	37	50
47330	1"	27	1.88	48	5.75	146	9.63	244	4.00	102	148	67	25
47340	1-1/4"	35	2.00	51	7.25	184	11.13	283	4.63	117	232	105	20
47350	1-1/2"	41	2.00	51	8.25	210	13.13	333	5.38	137	329	149	15
47360	2"	53	2.00	51	9.50	241	15.75	400	6.50	165	525	238	10
47365	2-1/2"	63	3.00	76	10.5	267	17.50	445	7.25	184	932	423	120*
47370	3"	78	3.18	81	13.0	330	21.13	556	9.00	229	1515	687	100*
47375	3-1/2"	91	3.25	83	15.0	381	26.13	664	10.88	276	2200	998	81*
47380	4"	103	3.38	86	16.0	406	26.25	667	10.88	276	2575	1168	64*
47385	5"	129	3.38	92	24.0	610	35.88	911	14.88	378	4783	2170	1*
47390	6"	155	3.75	95	30.0	762	43.38	1102	18.00	457	7590	3443	1*

Available in standard sizes 90°, 60°, 45°, 30°, 22.5° bends. Dimensions & Weights are Nominal subject to change without notice.

Compliance: UL 6, ANSI C80.1

File No: E468552

