



*Linus Wall Paint for walls, ceilings and radiators.
Pinewood floor waxed with Allbäck Linseed Oil Wax,
Brown.*

Linus and Linseed Oil Wax for furniture

Provides a durable, washable and silky matte finish.

- Paint with Linus Wall Paint to achieve the desired coverage.
- Use a brush or roller.
- Let the paint dry thoroughly.
- Sand the surface with fine 180–220 sandpaper.
- Apply coloured or natural Linseed Oil Wax.
- Wipe down within an hour.
- Allow to dry.
- Surfaces painted with white Linus paint should be waxed using white Linseed Oil Wax.
- The colourless wax may turn slightly yellow.

Creating different shades with Linus

All colours of Linus Wall Paint can be mixed with each other. Linus paint cannot be mixed with Linseed Oil Paint to create different shades.

Linus Wall Paint and yellowing

Yellowing of the paint will occur if it is not exposed to light. It is a good idea to add a little grey to Linus paint that will be used in darker spaces.

Behind paintings, furniture etc. there will be a yellow patch. This will disappear by itself when the area is exposed to light again. Yellow patches can of course be painted over.

Linus Wall Paint may have a chemical reaction with certain plastic surfaces. If this happens, there will be a stronger smell when the first coat is applied. **Ventilate!** After this the paint will behave as normal.