



No. AJFS1704001318FF

Date: APR.13, 2017

Page 1 of 4



The following sample(s) was / were submitted and identified on behalf of the client as: Sample Description: VUE FOAM / P012V

SGS Ref No.: AJHL1704002142FT

Type/Style: P012V



Test Requested:

The Furniture and Furnishings (Fire) (Safety) Regulations 1988 S.I. No. 1324 (amended 1989, 1993 and 2010), Schedule 1, Part I, Ignitability test for foam in slab or cushion form.

As specified in above standard(s) and incorporated with using ignition source 5 of BS 5852: Part 2:1982.

Test Results: -- See attached sheet --

Conclusion: The tested sample Meets the Requirements of Schedule 1 Part I in Statutory Instrument 1988 No. 1324 (Amended 1989, 1993 and 2010) the Furniture and Furnishings (Fire) (Safety) Regulations.

Test Period:

Sample Receiving Date : APR.06, 2017 Test Performing Date : APR.06, 2017 TO APR.12, 2017

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou **Technical Manager**



In writing, this document is issued by the Company subject to its General Conditions of Ser uest or accessible at <u>http://www.sgs.com/er/Terms-and-Conditions</u>, aspx and, for electronic format nditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-Terms-and-Conditions/Terms-and-Conditions/Te</u> time of its interv nd this documer

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn 中国。浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com



No. AJFS1704001318FF Date: APR.13, 2017 Page 2 of 4

Test Conducted

The Furniture and Furnishings (Fire) (Safety) Regulations 1988 S.I. No. 1324 (amended 1989,1993 and 2010), Schedule 1, Part I, Ignitability test for foam in slab or cushion form.

Crib 5 Test (Ignition Source 5)

Conditioning

Prior to testing: The sample was conditioned at least 72 h in indoor ambient conditions and 16 h in an

atmosphere having a temperature of 20 ± 5 °C and a relative humidity of 50 ± 20 %.

At time of testing: Temperature between 15° C ~ 30° C and Relative humidity between 20% ~ 70%.

Test results

The following test results relate only to the ignitability of the combination of materials under the particular condition of test. They are not intended as a means of assessing the full potential fire hazard of the materials or products in use.

(A) Progressive smouldering

Criteria of failure (Clause 4.1 of BS 5852 part 2:1982)		2 nd
4.1 b) – Any composite that product externally detectable amounts of smoke, heat or glow 60 min after ignition of the crib.		NO
4.1 c) – Any composite that displays escalating combustion behaviour so that it is unsafe to continue the test and requires forcible extinction.	NO	NO
4.1 d) – Any composite that smoulders until it is essentially consumed within the test duration relevant to the source		NO
4.1 e) – Any composite that smoulders to the extremities of the specimen viz. upper or lower margins, either side or to its full thickness, within the duration of the test.		NO
4.1 f) – Any composite that, on the final examination, shows evidence of charring other than discolouration, more than 100 mm in any direction apart from upwards from the nearest part of the original position of the source.		NO

(B) Flaming

Criteria of failure (Clause 4.2 of BS 5852 part 2:1982)		2 nd
4.2 b) – Any composite that continues to flame for more than 10 minutes after the ignition of the crib.		NO
4.2 d) – Any composite that displays escalating combustion behaviour so that it is unsafe to continue the test and forcible extinction is required.	NO	NO
4.2 e) – Any composite that burns until it is essentially consumed within the test duration relevant to the source.		NO
4.2 f) – Any composite on which any flame front reaches the lower margin, either side or passes through the full thickness of the specimen within the duration of the test.	NO	NO

To be continued....



Clience June was agreed in winding, this document is issued by the Company subject to its certrefal Collaboration of SerVice printed printed overleaf, available on request or accessible at <u>http://www.sab.com/into/fmms.adc.Con/libns.aspx</u> and, for electronic format documents, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this documents advised that information contained herein of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is transaction from exercising all their rights and obligations under the transaction document. This document is unaveliations approach to the transaction from exercising all their rights and obligations under the transaction forgery or faisification of the content or experiment is unaveliated of the Company's sole responsibility is to its Client and this document does not exonerate parties to a spearance of this document is unaveliated and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the resultation in the territor only to the sample(b) lested and such sample(b) are featured for 30 days only. Add3 are may all their right to the sample(b) lested and such sample(c) are featured to as to telephone;(86-75) 8307 Add3 are such to the such that the such

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 501825 f (86-572) 501825 f (86-572) 501825 f (86-57

Member of the SGS Group (SGS SA)



No. AJFS1704001318FF

Date: APR.13, 2017

Page 3 of 4

(C) Mass Loss

Criteria (Clause 5 in Schedule 1 of UK Regulations)	1 st	2 nd
If failure against the criteria of clause 4 of BS 5852:Part 2 has occurred but only by way of damage exceeding the limits defined in clause 4.1(e), 4.1(f) and 4.2(f) and provided that the resultant mass loss is less than 60g the foam passes the ignitability test.	21g	25g

Test Details:

Specimen No.		1 st	2 nd
Progressive smouldering (PS) or Flaming (F)		NO	NO
Duration of	Ignition source (min, sec)	2min21s	2min17s
	Flames (min, sec)	3min07s	3min20s
	Smoke (min, sec)	5min49s	5min52s
Extent of damage of horizontal component	Foam - Width (mm)	96	116
	Foam - Length (mm)	50	77
	Foam - Depth (mm)	42	46
Extent of damage of vertical component	Foam - Width (mm)	114	120
	Foam - Depth (mm)	50	40
Damage exceeds limits of clauses 4.1(e), 4.1(f) or 4.2(f)		NO	NO
Initial weight before test (g)		6966	6959
Finial weight after test (g)		6945	6934
Resultant mass loss (g)		21	25
Reason for failure (Ref to failure code)			
Finial examination of progressive smouldering (9.4)		NO	NO
Comments & observations			
Overall result		PASS	PASS

To be continued....



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sos.com/en/Terms-and-Conditions.asay and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sos.com/en/Terms-and-Conditions.Terms-and-Conditions.Terms-Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document to entot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / Inspection report & certificate, please contact us at telephone:(86-755) 8307

No. 301, Sunlight Road, 2 Block, Sunlight Rodusty Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 501825 f (86-572) 501825 f (86-5



No. AJFS1704001318FF

Page 4 of 4

Photo Appendix:

Details of sample:

Color: White

This foam sample of approximate density of 67.6 kg/m³.



SGS authenticate the photo on original report only *** End of Report ***



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.gsc.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.gsc.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a except in hill, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extend the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or remail: CN.DocctexReges.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 501825 f (86-572) 501825 f (86-572) 501825 f (86-5