



***Congratulations!***

**You are the new owner of TTRacing Duo V3!**

**Flip to the back to get started!**

**Thank you for your support!**

<p><b>A</b></p>	<p><b>B</b></p>	<p><b>C</b></p> <p>TÜVRheinland<sup>®</sup> CERTIFIED</p>
<p>CASTORS x5                      BASE x1                      GAS LIFT x1</p>		
<p><b>D</b></p>	<p><b>E</b></p>	<p><b>F</b></p> <p>Ø6*Ø18</p>
<p>GAS LIFT COVER x1                      MECHANISM x1                      WASHER x4</p>		
<p><b>G</b></p> <p>M6*20</p>	<p><b>H</b></p> <p>M6*25</p>	<p><b>I</b></p> <p>M6</p>
<p>SCREWS x4                      SCREWS x8                      HEX WRENCH x1</p>		
<p><b>J</b></p>	<p><b>K</b></p>	<p><b>L</b></p>
<p>ARMREST BARS x2                      SIDE CAPS x8                      SEAT CUSION x1</p>		
<p><b>M</b></p>	<p><b>O</b></p>	
<p>BACKREST x1</p>		

**1**

1.1 Attach the castors to the base by firmly pressing them into the holes under the base.

1.2 Insert the gas lift into the hole in the middle of the base.

**2**

Attach the mechanism to the bottom of the seat cushion using four G screws and washer

**3**

Attach the two armrests to the side of the seat cushion using four H screws.

**NOTE:**  
Do not over-tighten the screws to better preserve the condition of the chair

**4**

Attach the four sides of the chair using the four H screws

**5**

5.1 Attach the two halves of the chair together by inserting the gaslift into the mechanism piece.

**COMPLETED**

Attach the side caps to the eight sides of the chair using the four K side caps

Check that all screws are tight and enjoy your new chair!