



POST-PROCESSING:

THE DIRTY LITTLE 3D PRINTER SECRET
NO ONE TALKS ABOUT. **UNTIL NOW.**

Specifications:

- Build Size: 12in. X 8in. X 6in. (300mm x 200mm x 150mm)
- Layer Thickness: 0.25mm (250 μ)
- Workstation Compatibility: 64-bit Operating System, x64-based processor; Windows[®] 7, 8 or 10
- Network Connectivity: Ethernet 10/100, or USB stick
- Size: 21.4in. tall X 36in. wide X 25.4in. deep (543mm x 915mm x 644mm)
- Weight: 135lbs. (61kg)
- Power requirements: Universal power 100-240VAC, 750W
- 15°C – 30°C (59°F – 86°F) Operating Environment Temperature
- 20% - 60% Relative Humidity
- Regulatory Compliance: FCC, RoHS, NRTL
- Special Facility Requirements: None



To learn more, email us at: info@rize3d.com or call +1 978-699-3085.



Rize Inc., 4C Gill Street, Woburn, MA 01801 USA | www.rize3d.com

© 2016 Rize Inc. All rights reserved. Rize, the Rize logo, APD and Rizium are pending trademarks or registered trademarks of Rize Inc. All other company and product names are pending trademarks or registered trademarks of their respective holders.