



Flex digital printing



BF PRINT00
WHITE GLOSS 90 MY




BF PRINT01
WHITE MATT 90 MY




BF PRINT02
CLEAR MATT



BF PRINTSU
SUBLISTOP WHITE MATT



BF PRINTREF
REFLEX 150 MY



BF GID
GLOW IN THE DARK



BF PRINTTOP/G
WHITE GLOSS 60 MY



BF PRINTTOP/M
WHITE MATT 60 MY

Flex digital printing sheets A4-A3



BF PRINT20
LASER TRANSPARENT FILM 30 MY

Digital printing Gimme5 Evo



FIVEBFPRINT01
WHITE MATT 80 MY



FIVE BFPRINT01 EVO

FIVE BFPRINT01 is a polyurethane white opaque film printable with solvent, eco-solvent and Latex inks suitable for heat transfer **IN ONLY 4 SECONDS** on cotton fabrics, polyester and acrylic garments. Thanks to its self-adhesive PET film carrier even very small letters and logos can be easily cut by all current cutting plotters after the printing process. We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer, and then remove it while hot. **FIVE BFPRINT01** can be pressed on T-shirts, sportswear or uniforms for work. **FIVE BFPRINT01** does not contain PVC, plasticizers or heavy metals and is certified as per Oeko-Tex Standard 100 Class I requirements.

SUGGESTED FABRICS: cotton, polyester, mixed, printed with NON sublimatic colors.

CUT: cutting plotter, 45° blade, laser.
Wait at least 8 hours after the printing process.

WASHING: wait 12 hours after application.

Minimum cutting size **0,5 cm**

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

| | | | | |
|-------------------|-----------------|--------|----------------|-------------|
| THICKNESS 80 μ | MATTE FINISHING | OPAQUE | ADHESIVE LINER | PRINT & CUT |
| | | | | |

APPLICATION

TEMPERATURE
140°C - 285°F



4"



3,5 bar



LINER REMOVAL
HOT



WASHING

40°



STANDARDS:
Oeko-Tex Standard 100 Class I.

CONFIDENCE
IN TEXTILES
Tested for harmful substances
according to Oeko-Tex® Standard 100
15CX00005 CENTROCCOT

BF PRINT00/01

BFPRINT00 (semi-glossy) and BFPRINT01 (matte) are two polyurethane white films printable with solvent, eco-solvent and latex inks and are suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Very small letters and logos can be easily cut by all current cutting plotters after the printing process thanks to their ultimate self-adhesive PET film carrier. We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer, and then remove it while hot. **BFPRINT00 and BFPRINT01** can be pressed on T-shirts, sportswear or uniforms for work. **BFPRINT00 and BFPRINT01** do not contain PVC, plasticizers or heavy metals and are certified as per Oeko-Tex Standard 100 Class I requirements.

SUGGESTED FABRICS: cotton, polyester, mixed, printed with NON sublimatic colors.

CUT: cutting plotter, 45° blade, laser.
Wait at least 8 hours after the printing process.

WASHING: wait 12 hours after application.

Minimum cutting size **0,5 cm**

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

| | | | | | |
|-------------------|------------------|-----------------|--------|----------------|-------------|
| THICKNESS 90 μ | GLOSSY FINISHING | MATTE FINISHING | OPAQUE | ADHESIVE LINER | PRINT & CUT |
| | | | | | |

APPLICATION

TEMPERATURE
140°C - 285°F



10"



3,5 bar



LINER REMOVAL
HOT



40°



STANDARDS:
Oeko-Tex Standard 100 Class I.

CONFIDENCE
IN TEXTILES
Tested for harmful substances
according to Oeko-Tex® Standard 100
15CX00005 CENTROCCOT

BF PRINT02

BF PRINT02 is a polyurethane transparent film, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Thanks to its self-adhesive PET film carrier small letters and logos can be easily cut by all current cutting plotters after the printing process. **BFPRINT02** can be pressed on T-shirts, sportswear or uniforms for work.

SUGGESTED FABRICS: cotton, polyester, mixed, printed with NON sublimatic colors.

CUT: cutting plotter, 45° blade, laser.

LINER REMOVAL: wait 5 seconds after pressing.

WASHING: wait 12 hours after application.

Minimum cutting size **2,0 cm**

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

| | | | | |
|-------------------|-----------------|-------------|----------------|-------------|
| THICKNESS 50 μ | MATTE FINISHING | TRANSPARENT | ADHESIVE LINER | PRINT & CUT |
| | | | | |

APPLICATION

TEMPERATURE
150°C - 305°F



10"



3,5 bar



LINER REMOVAL
SEMI-HOT



40°



BF PRINTSU

BF PRINTSU is a polyurethane block-out film printable with all solvent, eco-solvent and latex based inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. **BF PRINTSU** is specially formulated to block the pigment migration from sublimation dyed textiles and keep any graphic looking bright on any kind of polyester garment! Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process. We recommend using BF MYLAR as a transfer tape and as a protection during the heat transfer, and then remove it while hot. **BFPRINTSU** can be pressed on T-shirts, sportswear or uniforms for work.

SUGGESTED FABRICS: polyester, printed with sublimatic colors.

CUT: cutting plotter, 45° blade.
Wait at least 8 hours after the printing process.

WASHING: wait 12 hours after application.

Minimum cutting size **2,0 cm**

COMPOSITION
PU Polyurethane

TECHNICAL FEATURES

| | | | | |
|--------------------|-----------------|--------|----------------|-------------|
| THICKNESS 120 μ | MATTE FINISHING | OPAQUE | ADHESIVE LINER | PRINT & CUT |
| | | | | |

APPLICATION

TEMPERATURE
140°C - 285°F



10"



3,5 bar



LINER REMOVAL
HOT



40°



BF PRINTTOP G/M

BFPRINT TOP/G (semi-glossy) AND BFPRINT TOP/M1 (matte) are two thin polyurethane white films printable with solvent, eco-solvent and latex inks and are suitable for heat transfer on cotton fabrics, polyester, nylon Lycra and acrylic garments. Very small letters and logos can be easily cut by all current cutting plotters after the printing process thanks to their ultimate self-adhesive PET film carrier; we recommend the BF MYLAR film as a transfer tape and as a protection during the heat transfer, and then remove it while hot. **BFPRINT TOP/G (semi-glossy) AND BFPRINT TOP/M1 (matte)** can be pressed on T-shirts, sportswear or uniforms for work.

- SUGGESTED FABRICS:** cotton, polyester, mixed, nylon, printed with NON sublimatic colors.
- CUT:** cutting plotter, 45° blade, laser.
Wait at least 8 hours after the printing process.
- LINER REMOVAL:** wait 5 seconds after pressing.
- WASHING:** wait 12 hours after application.

Minimum cutting size

1,0 cm

COMPOSITION
PU Polyurethane



TECHNICAL FEATURES

THICKNESS

60 μ



TOP G

semi-glossy



TOP M

matte



OPAQUE



ADHESIVE LINER



PRINT & CUT



APPLICATION

TEMPERATURE
145°C - 295°F



8"



3,5 bar



LINER REMOVAL

HOT



WASHING

40°



STANDARDS:

Oeko-Tex Standard 100 Class I.



BF PRINTREF

BF PRINTREFLEX is a re°ective heat transfer film, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments. thanks to its very good opacity **BF PRINTREF** can be used on both light and dark garments and can be pressed on T-shirts, sportswear or uniforms for work.

- SUGGESTED FABRICS:** cotton, polyester, mixed, printed with NON sublimatic colors.
- CUT:** cutting plotter, 45° blade, laser.
Wait at least 8 hours after the printing process.
- LINER REMOVAL:** wait 5 seconds after pressing.
- WASHING:** wait 12 hours after application.

Minimum cutting size

1,0 cm

COMPOSITION
PU Polyurethane



TECHNICAL FEATURES

THICKNESS

150 μ



GLOSSY FINISHING



OPAQUE



PRINT & CUT



APPLICATION

TEMPERATURE
150°C - 305°F



10"



3,5 bar



LINER REMOVAL

SEMI-HOT



WASHING

40°



FINISHING REFLEX



BF PRINT01



BF PRINT00



BF PRINT TOP/M



BF PRINT TOP/G