

Texilac Discharge Series

Code 1674--

PRODUCT DESCRIPTION

Two-component inks for discharge textile printing.

APPLICATION FIELDS

Discharge textile printing. For ready-to-wear or pre-cut cotton articles, dyed with dischargeable dyes.


GENERAL FEATURES

- High opacity onto dark substrates
- Very soft touch
- Good stability in the screen

EQUIPMENT

Indicated for using onto automatic, semi-automatic and manual machines.

PRODUCT RANGE

TEXILAC DISCHARGE LB Code 167462		<ul style="list-style-type: none"> • Very bright colours • High opacity onto dark substrates • Two-component ink: add 5% <i>Texilac Corrodente PM</i>
TEXILAC DISCHARGE WHITE Code 167464		<ul style="list-style-type: none"> • High whiteness • High opacity onto dark substrates • Two-component ink: add 5% <i>Texilac Corrodente PM</i>
TEXILAC CORRODENTE PM Code 167465		<ul style="list-style-type: none"> • Discharge agent • Compatible with <i>Texilac Discharge LB</i> and <i>Texilac Discharge White</i> • addition % = 5%
TEXILAC DISCHARGE LF Code 167469		<ul style="list-style-type: none"> • The printed article does not require washing before wearing • Very bright colours • Two-component ink: add 5% <i>Texilac Corrodente LF</i>
TEXILAC CORRODENTE LF Code 167470		<ul style="list-style-type: none"> • Discharge agent • Compatible with <i>Texilac Discharge LF</i> • addition % = 5%



SPECIAL INSTRUCTIONS

- Always test the printing characteristics, before starting production.
- Always check curing conditions. The addition of additives could require higher temperature or longer time.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

WARNING

This technical data sheet does not replace either the Safety Data Sheet or the specific Conformity Declaration. These documents may be required to our SHEQ (Product safety office), at the following e-mail address: safety@eptainks.com

The technical data sheet does not relieve the printer, who remains the only responsible of the respect of the regulations, the specifications and the related required certifications of the finished items.