

CAT6A DIN RAIL MOUNTED COUPLER

DESCRIPTION

The DYNAMIX CAT6A DIN mount shielded RJ45 coupler is the perfect solution for joining two shielded network patch leads in an industrial networking installation.

FEATURES

- Cat.6A/Class EA Screened In-line Coupler, RJ45 F/F
- For mounting on DIN-Rail TH35 acc. to DIN EN60715
- 1 DU (>18mm) width (DIN 43880)
- Side-by-side mountable
- With earthing spring
- IP20 Water and dust resistant
- 4PPoE compliant
- Supplied with Dust Cover
- Durability: 750 mechanical cycles



PRODUCT CODE	DESCRIPTION	COLOUR
DINC6AS	DIN Rail Mounted Coupler, C6A STP	Grey

SPECIFICATIONS

Installation	DIN Rail mounting, 1 DU
Technology	TH35
Design	CAT6A shielded
Water & Dust Resistant	IP20
Coupler	RJ45, Female to Female
Ethernet	10 GBit (IEEE 802.3an), PoE, PoE+
Measurements	18mm x 26.30mm x 34.50mm (WxHxD)
Material	Plastic
Compliant	4PPoE
Colour	Grey

ALSO AVAILABLE:

<p>DINUKS8P</p>  <p>8-Port unloaded keystone DIN rail-mount shielded enclosure with rotatable modules.</p>	<p>DIN0021</p>  <p>1 Port Keystone to DIN Mount Metal Adapter Plate</p>	<p>DIN0022</p>  <p>2 Port Keystone to DIN Mount Metal Adapter Plate</p>	<p>DIN0023</p>  <p>3 Port Keystone to DIN Mount Metal Adapter Plate</p>
--	---	--	---

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at contactus@dynamix.co.nz

Last updated: 16 June 2021