

12 CORE INDOOR/OUTDOOR FIBRE TERMINATION BOX

FEATURES:

- Designed for termination of up to 12 core optical fibre
- Wall mounted for indoor & outdoor use
- Waterproof & dust-tight (IP65 Rated)
- Suitable for 8x SC simplex or 8x LC duplex adapters
- Lockable UV stabilised plastic housing
- Fixed Fibre Support Bracket
- Compatible with PLC optical splitter with maximum OD ratio 1:8
- Dimensions: 220 x 180 x 50mm
- Includes: 12x cable ties, 3x screws, 2x sets number stickers (1-12) & 8x splice protectors









FWEIO-12 with 8 SC Adapters Installed

12 Core Fibre Splice Cassette

IP65 Rated Fibre Termination Box

COMPANION PRODUCTS FOR USE WITH THE FWEIO-12 FIBRE TERMINATION BOX



A-FIBLCLC-D

Fibre LC to LC Duplex Multimode Joiner, PhBr Sleeve, Beige colour



A-FIBLCLC-DSM

Fibre LC to LC Duplex Singlemode Joiner, Ceramic Sleeve, Blue colour



A-FIBSCSC-S

Fibre SC to SC Simplex Multimode Joiner, PhBr Sleeve, Beige colour




A-FIBSCSC-SSM

Fibre SC to SC Simplex Singlemode Joiner, Ceramic Sleeve, Blue colour

FIBRE OPTIC ADAPTERS

FEATURES:

- Every pigtail is tested to below 0.3dB insertion loss
- Full traceability & test certification supplied with each assembly
- 900µm tight buffer fibre optic cable
- 6/12 Pack colour coded to International/New Zealand standards
- Lifetime Warranty



CONNECTORS	SINGLE 2M	6 PACK 2M COLOUR CODED 0S2	12 PACK 2M COLOUR CODED
LC MM OM3	FPT-OM3LC	FPT-OM3LC-6	FPT-OM3LC-12
SC MM OM3	FPT-OM3SC	FPT-OM3SC-6	FPT-OM3SC-12
LC MM OM1	FPT-OM1LC	FPT-OM1LC-6	FPT-OM1LC-12
SC MM OM1	FPT-OMISC	FPT-OM1SC-6	FPT-OM1SC-12
LC SM OS1	FPT-OS1LC	FPT-OS1LC-6	FPT-OS1LC-12
SC SM OS1	FPT-OS1SC	FPT-OS1SC-6	FPT-OS1SC-12