

## FIBRE INLINE ENCLOSURE

The inline enclosure is suitable for protecting fibre cable splices in straight through and branching applications. Its well-engineered, injection molded outer body makes it impenetrable to the elements. It can protect splices and ensure reliability with usage in ambient temperatures from -40°C to +65 °C. It can be placed in aerial, underground, or duct mounted locations.

### FEATURES:

- Holds 24 to 114 splices
- Easy to re-enter
- 3 cable entries at each end
- Termination and splice kit included
- Airtight and waterproof integrated seal
- Ideal for cable repair
- RoHS compliant
- Can be used in through, branch or mid span splice locations
- Suitable for aerial, underground duct or direct burial applications
- IP68 up to 1.5m water depth



### PRODUCT SPECIFICATIONS

Max. Trays	8
Cable Entry Points	6
Suitable for Cable Diameter	8mm ~ 16mmØ
Sealing Rating	IP68
Sealing Method for all Entry and Exit	Mechanical (compression)
Colour	Black
Material	ABS
RoHS Compliant	Yes
Optimal Operating Temperature	-40°C ~ +65°C
Dimensions (w x d x h)	INLINE01: 210 x 450 x 90.5mm INLINE03: 210 x 450 x 90.5mm INLINE05: 216 x 450 x 150mm
Weight	INLINE01: 2kg INLINE03: 2kg INLINE05: 3kg

### PRODUCT CODES

Model Code	Splice Count	Size
INLINE01	24	210 x 450 x 90.5mm
INLINE03	72	210 x 450 x 90.5mm
INLINE05	114	216 x 450 x 150mm