

USB / PS/2 KVM Switch, PS/2 Console

MODEL CODE	TYPE
UNV104D BK	4 PC USB/PS/2, PS/2 Console
UNV108D BK	8 PC USB/PS/2, PS/2 Console
UNV116D BK	16 PC USB/PS/2, PS/2 Console

- USB/VGA Cables Included
- Rackmount Kits Included with 8 and 16 port

OPTIONAL SLIMLINE CABLES	TYPE	LENGTH
KNVP-1	PS/2	1.8M
KNVP-3	PS/2	3M
KNVP-6	PS/2	6M
KNVU-1	USB	1.8M
KNVU-3	USB	3M
KNVU-5	USB	5M

Control 4, 8 or 16 Computers from a single Keyboard, PS/2 Mouse and VGA Monitor



KNVU (Included)

KNVP (Optional)



FEATURES

- Cascade configuration expands system capability up to 136 servers
- 1RU height form factor saves rack spaces
- Supports video resolution 1929 x 1440
- Unique cables for secured connection
- Auto-scan function automatically selects computers sequentially
- Supports Microsoft IntelliMouse (Pro)
- Assigns computers unique and meaningful names
- Identifies and selects computers by the names
- Programmable scan filters unused computers
- Stores system settings and name entries to non-volatile memory
- Password security locks computer from unauthorised access
- Gains complete control with easy-to-use OSD interface
- Hotkey functions allow easy computer access
- Keyboard states automatically saved and restored when switching computers
- Operating system independent and transparent to all applications
- Plug n play system configuration
- Keyboard and mouse can be hot plugged at any time
- DDC2B compatible
- Optional multimedia module supports microphones and stereo speakers



UNV104D BK



UNV116D BK

Desktop/Rackmount PS/2 KVM Switch

MODEL CODE	TYPE
KNV102 BK	2 PC PS/2
KNV104 BK	4 PC PS/2
KNV104D BK	4 PC OSD PS/2
KNV108 BK	8 PC PS/2
KNV108D BK	8 PC OSD PS/2
KNV116D BK	16 PC OSD PS/2

Control multiple computers with one keyboard, mouse and monitor

- Cables and rackmount kits purchased separately

RACKMOUNT KITS

KNV-RMK04 BK	Supports KNV104 series
KNV-RMK08 BK	Supports KNV108 series
KNV-RMK16 BK	Supports KNV116 series

CABLES REQUIRED

CABLES REQUIRED	LENGTH
KNVM-1	1.8M
KNVM-3	3M
KNV-CBK500	5M
KNV-CBK600	6M
KNV-CBKM10	10M
KNV-CBKM15	15M
KNV-CBKM20	20M



FEATURES

- VGA resolution up to 1920 x1440
- Keyboards and mice can be hot plugged at any time
- Hot-key function
- Cascade system capability
- Microsoft IntelliMouse (Pro) support
- PS/2 & Serial mouse support
- Auto-scan for easy monitoring
- Standard or 3 in 1 cables
- Tilt-free rackmount kit available
- Operating system independent, transparent to all applications



KNV104 BK



The Monitor, PS/2 keyboard & PS/2 mouse plug directly into the KVM switch
Computers are connected to the KVM switches via tangle free 3 in 1 cables

