

6G

PADG-122 (2 Port)

PADG-124A (4 Port)



2/4-Port **Dual-View** DisplayPort KVM Switch 3840 x 2160@60Hz (4:4:4)

► Specifications

		PADG-122	PADG-124A
Resolution (Max.)		3840 x 2160@60Hz	
Console Port		1	1
Computer Port		2	4
Front Panel Push Button		1	4
Hot plug-and-play		Yes	Yes
Automatic scan interval		3, 8, 15, 30, seconds	
Cable Length		3M (10ft) for USB	
Computer ready LED, (green)		2	4
Computer selected LED, (red)		2	4
Computer Interface	USB 2.0 Port	USB-B x 2	USB-B x 4
	Video Interface	DisplayPort x 4 (Dual-View x 2 PCs)	DisplayPort x 8 (Dual-View x 4 PCs)
	Audio Jack (Speaker)	2 Set	4 Set
Console Interface	USB-HID Port	USB-A x 2	
	USB 2.0 Port	USB-A x 2	
	Monitor	DisplayPort x 2 (Dual-View)	
	Audio Jack (Speaker)	1 Set	
Hotkey		Yes	
H x W x D (mm)		60 x 160 x 100	60 x 220 x 130
Power supply		DC 9~12V	

► Features

- 2/4 Computers Share up to 4 Different USB Peripherals (KB + MS + 1 USB 2.0 Device)
- Support Dual-View DisplayPort
- Support USB Console
- Support DisplayPort Video with The Resolution up to 3840 x 2160@60Hz
- Front Panel Push Buttons for Easy Computer Selection
- No Drivers Needed or Software Required for Keyboard and Mouse Operation
- Support Keyboard and Mouse Plug-n-play
- Buzzer Sound for Computer Switching Confirmation
- Activate Auto Scan by Front Buttons Pressing
- Hotkey Functions Allows Easily Computer Access
- Selectable Scan Time Interval
- Support Windows and Mac Host Systems

► Connection Pattern

