

EZ Connect[™] N

SMCWUSBS-N4

150 Mbps Wireless-N USB Adapter



Product Overview

The EZ Connect[™] Wireless-N USB 2.0 Adapter enables Wireless-N connectivity to your desktop or notebook computer and provides improved throughput of up to 150 Mbps compared to existing 802.11g technology. With security being a key consideration, the latest WPA and WPA2 wireless encryption standards are supported, which prevent unauthorized access to wireless networks and ensure data is secure. The SMCWUSBS-N4 includes an EZ Connect[™] wizard, which guides you step-by-step through the installation process. Once installed, the WLAN utility allows you to scan for available wireless networks and manage multiple network profiles, enabling future connections to be instantaneous.

Key Features and Benefits

Faster Speeds

SMCWUSBS-N4 Wireless-N USB 2.0 Adapter delivers amazing speeds of up to 150 Mbps.

Advanced Security

SMCWUSBS-N4 supports WEP64/128, WPA/WPA2 Enterprise and PSK for a comprehensive security selection that fits your requirement.

Easy to Use

The EZ Connect[™] wizard provides quick step-by-step ease-of-use of the SMCWUSBS-N4. An intuitive user interface makes monitoring and other configurations a breeze.

Easy Secure Connections

With a WPS button, secure connections can be easily established by simply clicking a button.

Application Diagram -





EZ Connect[™] N

Features -

Models of Operation

Station: Infrastructure or Ad-Hoc mode

Physical

USB 2.0

Security Features

WEP 64/128-bit encryption WPA/WPA2-PSK (Pre-shared Key) WPA/WPA2 Enterprise (802.1X) WPS - PIN and Button

Quality of Service

WMM (Wi-Fi Multimedia)

Standards

IEEE 802.11b IEEE 802.11g Compatible with IEEE 802.11n

Radio Data Rate

11b: 1/2/5.5/11 Mbps 11g: 6/9/12/18/24/36/48/54 Mbps

Modulation

11b: CCK, QPSK, BPSK 11g: OFDM

Media Access Protocol

CSMA/CA with ACK

Operating Frequency

2.4 ~ 2.4835 GHz

OS Compatibility

Microsoft Windows XP, Vista, Windows 7

Package Contents

SMCWUSBS-N4 150 Mbps Wireless -N USB Adapter Quick Installation Guide GPL CD Warranty Information Card

Dimensions

89 x 26 x 11 mm (3.5 x 1.0 x 0.4 in.)

Weight

19g (0.67 oz)

Operating Temperature

Operating: 0 °C to 40 °C (32 °F to 104 °F) Storage: -40 °C to 70 °C (-40 °F to 158 °F)

Humidity

Operating: 10% to 90% RH (non-condensing) Storge: 5%-90% RH (non-condensing)

Warranty

Please check www.smc.com for the warranty terms in your country/region.

Physical Connection



©2012 SMC Networks. EZ SwitchTM is a trademark of SMC Networks. Other trademarks or registered trademarks are the property of their respective owners. Information is subject to change without notice. All rights reserved.



Edge-Core Networks Corporation Worldwide Corporate and Sales Headquarters

No. 1 Creation Road III, Hsinchu Science Park, 30077, Taiwan, R.O.C. Tel: +886 3 5638888 Fax: +886 3 6686111



Singapore

1 Coleman Street #07-09, The Adelphi Singapore 179803 Tel: 65-63387667 Fax: 65-63387767

Check www.smc-asia.com or www.smc.com for your local country contact information