

APC Smart-UPS SRT 1000VA RM 230V Network Card

SRT1000RMXLI-NC




- Includes: CD with software, Communication cable, Country-specific detachable power cord, Documentation CD, Installation guide, Network management card, Rack mounting brackets, Rack mounting hardware, Rack mounting support rails, Temperature probe, USB cable, Warranty card

Output	
Output power capacity	1.0kWatts / 1.0kVA
Max Configurable Power (Watts)	1.0kWatts / 1.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (6) IEC 60320 C13
Bypass	Built-in bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	BS1363A British, IEC 60320 C14, Schuko CEE 7 / EU1-16P
Cord Length	6ft (1.8meters)
Input voltage range for main operations	50 - 150 40% load, 80 - 150V
Number of Power Cords	1

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Battery type	Lead-acid battery
Included Battery Modules	1
Typical recharge time	3hour(s)
Nominal Battery Voltage	48 V
Replacement Battery	APCRBC155 
Expected Battery Life (years)	3 - 5
Battery Charge Power (Watts)	97 Watts
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-SRT-1000VA-RM-230V-Network-Card (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Pre-Installed SmartSlot™ Cards	AP9631 (Available in Technical Tab on site)
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	432Joules

Physical	
Maximum Height	3.35inches (85MM, 8.5CM)
Maximum Width	17.01inches (432MM, 43.2CM)
Maximum Depth	19.88inches (505MM, 50.5CM)
Rack Height	2U
Net Weight	46.3lbs. (21.0KG)
Shipping weight	65.26lbs. (29.6KG)
Shipping Height	9.69inches (246MM, 24.6CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Width	23.39inches (594MM, 59.4CM)
Shipping Depth	29.49inches (749MM, 74.9CM)
Color	Black
Units per Pallet	12.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 50000ft (0 - 15240meters)
Audible noise at 1 meter from surface of unit	50.0dBA
Online thermal dissipation	317.0BTU/hr
Protection Class	IP20

Conformance	
Approvals	CE, EAC
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.