

Mini Digital Hygro-thermomter

USER MANUAL MODEL: B0119TH We thank you for the purchase of Baldr Mini Digital Hygro-thermomiter. It has been designed and constructed using innovative components and techniques to enable the perfect display of temperature and humidity by this device. Please read the instructions carefully to become familiar with the properties and functions, before you use the unit. For the start-jung of this device you require:

OVERVIEW



1x CR2032 battery (included)



Change temperature displaybetween Fahrenheit and Celsius

FEATURES

- 1. Temperature display in C/F
- 2. Temperature range: -40°C ~ + 60°C (-40°F ~140°F)
 3. Humidity display range: 10%~99%
- Comfort level indication
- Table standing, wall hanging or magnet attaching

GETTING STARTED

POWER ON

Remove the plastic tab from the battery compartment prior to use:

The LCD will display all digits and icons for 3 seconds, followed by the reading

TEMPERATURE

- 1. After power on, the temperature will display automatically. It will update reading each 10 seconds. 2. If you want to change between Fahrenheit and Celsius, press " C/F" button on the front.
- 3. Temperature display range: -40 \mathbb{F} ~140 \mathbb{F} (-40 $\mathbb{C}~\sim$ + 60 \mathbb{C}).
- 4. Accuracy: when temperature is between 10C \sim 40C , the accuracy is +/- 1.5C, if out of this range the accuracy will be +/- 5C. Temperature resolution:0.1 $\mathbb P$ (0.1 C).

HUMIDITY

It will display humidity after power on. The measuring range is: 10% - 99% Accuracy; for humidity between $40\% \sim 80\%$, it he accuracy is +/- 5%, if out of this range the accuracy will be +/- 7%.

COMFORT LEVEL INDICATION

- ☼ Comfortable: Temperature between 18C to 26C, and the humidity between 40%RH to 60%RH
- 44 Un-comfortable: Temperature lower than 10C or higher than 30C, and humidity lower than 30%RH or higher than 70%RH
- ♦ Normal Comfortable: Temperature between 10C to 17.9C or 26.1C to 30C, and the humidity between 30%RH to 39%RH or 61%RH to 70%RH

PRECAUTIONS

- Do not clean any part of the product with benzene, thinner or other solvent chemicals. When necessary, clean it with a soft cloth.
- Never immerse the product in water. This will damage the product.
- Do not subject the product to extreme force, shock, or fluctuations in temperature or humidity.
- Do not tamper with the internal components.
 Do not mix new and old batteries or batteries of different
- Do not mix alkaline, standard or rechargeable batteries with this product.
- Remove the batteries if storing this product for a long period of time.
- Do not dispose of this product as unsorted municipal waste. Collection of such waste separately for special treatment is necessary.

WARRANTY

BALDR provides a 1-year limited warranty on this productagainst manufacturing defects in materials and workmanship.

Warranty service can only be performed by our authorized service center. The original dated bill of sale must be presented upon request as proof of purchase to us, or our authorized service center.

The warranty covers all defects in material and workmanship with the following specified exceptions: (1) damage caused by accident, unreasonable use or neglect (including the lack or reasonable and necessary maintenance); (2) damage occurring during shipment (claims must be presented to the carrier); (3) damage to, or deterioration of any accessory or decorative surface;(4) damage resulting from failure to follow instructions contained in your owner's manual.

This warranty covers only actual defects within the product itself, and does not cover the cost of installation or removal from a fixed installation, normal set-up or adjustments, claims based on misrepresentation by the seller or performance variations resulting from installation-related circumstances.

To receive warranty service, the purchaser must contact with BALDR nominated service center for the problem determination and service procedure.

Thank you for your choice of BALDR products!



www.baldr.com

66-BALDRB0119-002