



FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JL

QTY	Parts List
1	Fuel Door Cover
1	Installation Instructions

Difficulty Level: Easy

Product Support

1-888-531-7183

info@combat4x4.com

Tool List
T40 Torx Bit
#2 Flat Head Screwdriver or pick

Product Image

WARNING:
YOU ARE WORKING ON THE FUEL SYSTEM!
TAKE PRECAUTIONS TO KEEP AWAY ANY SOURCE OF HEAT OR FLAMES.

Notes and Maintenance
Before you begin installation, read all instructions thoroughly.
Proper tools will improve the quality of installation and reduce the time required.
For black finishes, mild soap may be used to clean the product.
Periodic inspections should be performed to ensure all mounting hardware remains tight.
Mild automotive detergent may be used to clean the product. Do not use dish detergent, abrasive cleaners, abrasive pads, wire brushes or other similar products that may damage the finish.

Feedback
COMBAT OFF ROAD industry leading warranty. Register your purchase by visiting: www.combat4x4.com/registration
Be social, tag us on your install or out on the trail enjoying, use: #combat4x4 and #combatoffroad



Step 1

Open the gas cap and use the pick or a flat head screwdriver to remove it from the vehicle, retain for reuse.



Step 2

Remove the tail light from the left hand side of the vehicle body. Go into the back of the vehicle to perform this task.

Locate and remove the inside access cover for the mounting hardware used to hold the tail light on. You may need the pick or a screwdriver to do this.



Step 3

Using the T40 torx bit, remove the tail light mounting hardware. **CAUTION:** The fastener is plastic!

Also a 10mm socket will work here.





Step 4

Pull the tail light assembly out from the body, locate tab on inside of light assembly, push in tab using screwdriver to release from body.



Step 5

Disconnect the electrical harness connected to the tail light assembly. Do this by sliding the red tab and pushing down on the locking tab.



Step 6

Push in the clips on the rear side of the fuel cover to release it from the body (4 places) as you pull it out from the side.





Step 7

Remove the rubber gasket for reuse on the new fuel door.

(Extra gasket included if required)

Install the rubber gasket into the new fuel door in the same orientation.



Step 8

Line up the locating tab at the top of the fuel door with the top locating notch on the body of the jeep.



Step 9

With everything aligned, push the door into the body to lock the tabs into place, make sure it sits flush with the body of the jeep.





Step 10

Reinstall the fuel cap, pushing the lanyard tab back into place.



Step 11

Reinstall the tail light by reconnecting the electrical harness, ensure that you slide the red locking tab back into place.



Step 12

Line up the studs on the light with the vehicle body and push the tail light assembly back into position, secure with the original T40 plastic screw and tighten, carefully!





FUEL CONTAINMENT DOOR

Installation Instructions JEEP WRANGLER JL

Step 13

Re-secure the interior cover.



Step 14

ENJOY!



WARNING: Cancer
and Reproductive Harm -
www.P65Warnings.ca.gov