



# BENJAMIN MOORE NATURA™ INTERIOR WATERBORNE PAINT EGGSHELL K513

## Features

- Low odour
- Zero VOC\*
- Zero emissions\*\*
- Self priming on most surfaces
- 100% Acrylic
- Dries quickly to a beautiful, washable, and uniform eggshell finish
- Spatter-resistant
- Quick return to service

## Recommended For

New or previously painted interior wallboard, plaster and masonry, as well as primed or previously painted wood and metal. Provides a beautiful eggshell finish on walls and ceilings.





## General Description

Benjamin Moore Natura™ Interior Waterborne Eggshell (K513) is a premium quality, safer paint that offers zero VOC and zero emissions while providing a durable, washable and fade resistant finish. Benjamin Moore Natura™ Interior Waterborne Eggshell (K513) is ideally suited for residential applications. It is made with a patented, environmentally friendly formula that is virtually odourless.

## Limitations

- Do not paint when temperature of air and surface is below 10°C (50 °F)

## Product Information

<p><b>Colours: — Standard:</b> White (01)</p> <p><b>— Tint Bases:</b> Benjamin Moore® Gennex® Bases 1X, 2X, 3X, &amp; 4X</p> <p><b>— Special Colours:</b> Contact your Benjamin Moore Representative.</p> <p><b>Certification:</b> VOC compliant in all regulated areas</p>    <p><b>Required parameters are missing or incorrect</b></p>  <p>In addition to the certifications above, Benjamin Moore's Green Promise® designation means that this product has been tested by independent third parties and meets or exceeds the published chemical restriction and performance criteria included in the standards shown below.</p> <p>LEED®/LEED V4 - Low Emitting Product Credit, Building Product Disclosure Credit</p> <p>CHPS (Collaborative for High Performance Schools)</p> <p>MPI Green Performance™ Master Painters Institute MPI # 44, 44 X-Green, 144, 144 X-Green</p> <p>Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84</p> <p><b>WARRANTY:</b> We warrant satisfactory results if used according to label directions. If not satisfied, return the unused portion to place of purchase with sales receipt. Material will be replaced or purchase price will be refunded. Since we have no control over surface preparation or application, THIS LIMITED WARRANTY DOES NOT INCLUDE THE COST OF LABOUR FOR APPLICATION OF PAINT. BENJAMIN MOORE &amp; CO., LIMITED SHALL IN NO EVENT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING ECONOMIC LOSS. This limited warranty gives you specific legal rights and is applicable to products sold in Canada. You may also have other rights, which vary from province to province.</p> <p><b>Technical Assistance:</b> Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-800-361-5898, <a href="mailto:info@benjaminmoore.ca">info@benjaminmoore.ca</a>, <a href="http://www.benjaminmoore.ca">www.benjaminmoore.ca</a></p>	<table border="1"> <thead> <tr> <th>Technical Data◇</th> <th>Pastel Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>100% Acrylic Latex</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>44%</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td>34.8-39.5 sq. m. (375 – 425 Sq. Ft.)</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet 4.0 mils – Dry 1.8 mils</td> </tr> <tr> <td colspan="2">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td>– To Touch 30 Minutes – To Recoat 1-2 Hours</td> </tr> <tr> <td colspan="2">Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity</td> <td>110 ± 2 KU</td> </tr> <tr> <td>Flash Point</td> <td>None</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Eggshell (15-25 @ 85°)</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)</td> </tr> <tr> <td>Thin With</td> <td>See Chart</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Clean Water</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td>5.2 kg (11.5 lbs)</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)</td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>Volatile Organic Compounds (VOC)</b></td> </tr> <tr> <td colspan="2" style="text-align: center;">0 Grams / Litre*</td> </tr> <tr> <td colspan="2" style="text-align: center;">-Zero VOC post tint (any base and any colour)</td> </tr> <tr> <td colspan="2">*Zero VOC according to EPA Method 24</td> </tr> <tr> <td colspan="2">**Zero emissions detected according to CDPH/EHLB/Standard Method V1.1, 2010</td> </tr> </tbody> </table>	Technical Data◇	Pastel Base	Vehicle Type	100% Acrylic Latex	Pigment Type	Titanium Dioxide	Volume Solids	44%	Coverage per 3.79 L at Recommended Film Thickness	34.8-39.5 sq. m. (375 – 425 Sq. Ft.)	Recommended Film Thickness	– Wet 4.0 mils – Dry 1.8 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 30 Minutes – To Recoat 1-2 Hours	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.		Dries By	Evaporation, Coalescence	Viscosity	110 ± 2 KU	Flash Point	None	Gloss / Sheen	Eggshell (15-25 @ 85°)	Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)	Thin With	See Chart	Clean Up Thinner	Clean Water	Weight Per 3.79 L	5.2 kg (11.5 lbs)	Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)	<b>Volatile Organic Compounds (VOC)</b>		0 Grams / Litre*		-Zero VOC post tint (any base and any colour)		*Zero VOC according to EPA Method 24		**Zero emissions detected according to CDPH/EHLB/Standard Method V1.1, 2010	
Technical Data◇	Pastel Base																																														
Vehicle Type	100% Acrylic Latex																																														
Pigment Type	Titanium Dioxide																																														
Volume Solids	44%																																														
Coverage per 3.79 L at Recommended Film Thickness	34.8-39.5 sq. m. (375 – 425 Sq. Ft.)																																														
Recommended Film Thickness	– Wet 4.0 mils – Dry 1.8 mils																																														
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.																																															
Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch 30 Minutes – To Recoat 1-2 Hours																																														
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.																																															
Dries By	Evaporation, Coalescence																																														
Viscosity	110 ± 2 KU																																														
Flash Point	None																																														
Gloss / Sheen	Eggshell (15-25 @ 85°)																																														
Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)																																														
Thin With	See Chart																																														
Clean Up Thinner	Clean Water																																														
Weight Per 3.79 L	5.2 kg (11.5 lbs)																																														
Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)																																														
<b>Volatile Organic Compounds (VOC)</b>																																															
0 Grams / Litre*																																															
-Zero VOC post tint (any base and any colour)																																															
*Zero VOC according to EPA Method 24																																															
**Zero emissions detected according to CDPH/EHLB/Standard Method V1.1, 2010																																															

◇Reported VOC values are for all bases/colors.

## Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure before applying base coat. Cured plaster should be hard, have a slight sheen and maximum PH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound.

Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry.

**Difficult Substrates:** Benjamin Moore offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/vh-vs/prod/paint-peinture\\_e.html](http://www.hc-sc.gc.ca/vh-vs/prod/paint-peinture_e.html).

## Primer/Finish Systems

Benjamin Moore Natura™ Eggshell Finish is self-priming on most surfaces. Benjamin Moore Natura™ will act as its own primer, providing the optimal foundation for the subsequent finish coat. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. While the high quality of our products sometimes makes one-coat coverage achievable, Benjamin Moore recommends two coats of this product to achieve full colour development and to maximize paint film performance. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

### Wood, and Engineered Wood Products:

**Primer:** Benjamin Moore Natura™ Interior Waterborne Primer (K511)

**Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

**For Bleeding Woods such as Cedar and Redwood,** use Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Oil Based Primer (F024)

**Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

### Drywall:

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

### Plaster:

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

### Rough or Pitted Masonry:

**Primer:** Super Spec® Masonry Interior/Exterior Hi-Build Block Filler (K206)

**Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint, Semi-Gloss (K514)

### Smooth Poured or Pre-cast Concrete:

**Primer/Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

### Ferrous Metal (Steel and Iron):

**Primer:** Super Spec HP® Acrylic Metal Primer (KP04) or Super Spec HP® Alkyd Metal Primer (KP06)

**Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

**Non-Ferrous Metal (Galvanized & Aluminum):** All new metal surfaces must be thoroughly cleaned with Super Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

**Primer:** Not required on properly prepared surfaces

**Finish:** 1 or 2 coats of Benjamin Moore Natura™ Interior Waterborne Paint

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

## Application

Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed. See Chart below.

## Thinning/Clean up

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
<b>Brush:</b> Nylon / Polyester	No thinning necessary	Add K518 Extender or water:  Max of 236 ml (8 fl. oz.) to 3.79 L of paint  <b>Never add other paints or solvents.</b>
<b>Roller:</b> Premium Quality 9.5 mm roller cover		
<b>Spray:</b> Airless Pressure: 1500 -2500 psi Tip: 0.013-0.017		

**Clean up:** Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

**USE COMPLETELY OR DISPOSE OF PROPERLY.** Dry, empty containers may be recycled in a can-recycling program. **Local disposal requirements vary; consult your sanitation department or provincial-designated environmental agency on disposal options.**

## Environmental Health & Safety Information

**Use only with adequate ventilation.** Ensure fresh air entry during application and drying. Do not breathe spray mist or sanding dust. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL –** Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional health and safety information.**