



# ADVANCE<sup>®</sup> WATERBORNE INTERIOR ALKYD PRIMER K790

## Features

- Provides a total waterborne system for ADVANCE<sup>®</sup> Waterborne Interior Alkyd finishes
- Easy to apply
- Excellent levelling properties
- Excellent adhesion
- Sandable
- Spatter resistant
- Minimal odour
- Excellent for blocking household stains

## Recommended For

Ideal for interior doors, trim, cabinets, walls, and ceilings. For primed or previously painted wallboard, plaster, masonry, wood and metal.

## General Description

A premium quality waterborne alkyd primer formulated primarily to provide a sealed and sandable surface for ADVANCE<sup>®</sup> Waterborne Alkyd topcoats. Combines the qualities desired in an interior primer: Excellent adhesion, spatter proof, sandability, minimal odour, excellent flow and levelling, and household stain blocking.

## Limitations

- Not recommended for blocking tannin, sealing knots or over pine sap.
- Proper adhesion to existing enamel, catalyzed lacquers or synthetic surfaces will require sanding and priming with a specialty primer. See Primer/Finish Systems on page 2.

Product Information																																																																		
<p><b>Colours — Standard:</b> White White may be tinted to light pastels with up to 60 ml per 3.79 L of Benjamin Moore<sup>®</sup> Gennex<sup>®</sup> colorants. For best hiding results, tint to the approximate shade of the finish coat.</p>	<p><b>Technical Data</b> <span style="float: right;"><b>White</b></span></p> <table border="1"> <tr> <td>Vehicle Type</td> <td colspan="2">Waterborne Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td colspan="2">Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td colspan="2">41.5%</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td colspan="2">37.1 – 46.4 sq. m. (400 – 500 sq. ft.)</td> </tr> <tr> <td rowspan="2">Recommended Film Thickness</td> <td>– Wet</td> <td>3.6 mils</td> </tr> <tr> <td>– Dry</td> <td>1.5 mil</td> </tr> <tr> <td colspan="3">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td rowspan="2">Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td>– To Touch</td> <td>4-6 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>8 Hours</td> </tr> <tr> <td colspan="3">Advance's<sup>®</sup> full hardness and adhesion develop over time. Do not expose to heavy abrasion or return shelves/tabletops to service for at least 3-5 days to prevent damage to the finish. High humidity or cooler temperatures will prolong dry, recoat and cure times.</td> </tr> <tr> <td>Dries By</td> <td colspan="2">Evaporation, Oxidation</td> </tr> <tr> <td>Viscosity</td> <td colspan="2">100 ± 4 KU</td> </tr> <tr> <td>Flash Point</td> <td colspan="2">None</td> </tr> <tr> <td>Gloss / Sheen</td> <td colspan="2">Flat (&lt;5 @ 85°)</td> </tr> <tr> <td rowspan="2">Surface Temperature at Application</td> <td>– Min.</td> <td>10 °C (50 °F)</td> </tr> <tr> <td>– Max.</td> <td>32 °C (90 °F)</td> </tr> <tr> <td>Thin With</td> <td colspan="2">Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td colspan="2">Clean Water</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td colspan="2">5.38 kg (11.8 lbs)</td> </tr> <tr> <td rowspan="2">Storage Temperature</td> <td>– Min.</td> <td>4.4 °C (40 °F)</td> </tr> <tr> <td>– Max.</td> <td>32 °C (90 °F)</td> </tr> <tr> <td colspan="3" style="text-align: center;"><b>Volatile Organic Compounds (VOC)</b></td> </tr> <tr> <td colspan="3" style="text-align: center;">44 g/L</td> </tr> </table>	Vehicle Type	Waterborne Alkyd		Pigment Type	Titanium Dioxide		Volume Solids	41.5%		Coverage per 3.79 L at Recommended Film Thickness	37.1 – 46.4 sq. m. (400 – 500 sq. ft.)		Recommended Film Thickness	– Wet	3.6 mils	– Dry	1.5 mil	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.			Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch	4-6 Hours	– To Recoat	8 Hours	Advance's <sup>®</sup> full hardness and adhesion develop over time. Do not expose to heavy abrasion or return shelves/tabletops to service for at least 3-5 days to prevent damage to the finish. High humidity or cooler temperatures will prolong dry, recoat and cure times.			Dries By	Evaporation, Oxidation		Viscosity	100 ± 4 KU		Flash Point	None		Gloss / Sheen	Flat (<5 @ 85°)		Surface Temperature at Application	– Min.	10 °C (50 °F)	– Max.	32 °C (90 °F)	Thin With	Do Not Thin		Clean Up Thinner	Clean Water		Weight Per 3.79 L	5.38 kg (11.8 lbs)		Storage Temperature	– Min.	4.4 °C (40 °F)	– Max.	32 °C (90 °F)	<b>Volatile Organic Compounds (VOC)</b>			44 g/L		
Vehicle Type	Waterborne Alkyd																																																																	
Pigment Type	Titanium Dioxide																																																																	
Volume Solids	41.5%																																																																	
Coverage per 3.79 L at Recommended Film Thickness	37.1 – 46.4 sq. m. (400 – 500 sq. ft.)																																																																	
Recommended Film Thickness	– Wet	3.6 mils																																																																
	– Dry	1.5 mil																																																																
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.																																																																		
Dry Time @ 25 °C (77 °F) @ 50% RH	– To Touch	4-6 Hours																																																																
	– To Recoat	8 Hours																																																																
Advance's <sup>®</sup> full hardness and adhesion develop over time. Do not expose to heavy abrasion or return shelves/tabletops to service for at least 3-5 days to prevent damage to the finish. High humidity or cooler temperatures will prolong dry, recoat and cure times.																																																																		
Dries By	Evaporation, Oxidation																																																																	
Viscosity	100 ± 4 KU																																																																	
Flash Point	None																																																																	
Gloss / Sheen	Flat (<5 @ 85°)																																																																	
Surface Temperature at Application	– Min.	10 °C (50 °F)																																																																
	– Max.	32 °C (90 °F)																																																																
Thin With	Do Not Thin																																																																	
Clean Up Thinner	Clean Water																																																																	
Weight Per 3.79 L	5.38 kg (11.8 lbs)																																																																	
Storage Temperature	– Min.	4.4 °C (40 °F)																																																																
	– Max.	32 °C (90 °F)																																																																
<b>Volatile Organic Compounds (VOC)</b>																																																																		
44 g/L																																																																		
<p><b>— Tint Bases:</b> N/A</p>																																																																		
<p><b>— Special Colours:</b> Contact your Benjamin Moore representative.</p>																																																																		
<p><b>Certification:</b> <b>VOC compliant in all regulated areas.</b> Master Painters Institute MPI # 172 Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84</p> <div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p><b>Qualifies for</b> <b>LEED<sup>®</sup></b> <b>Credit</b> <b>(PRIMER)</b></p> </div> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <p><b>CHPS Certified</b> (Collaboration for High Performance Schools)</p> </div> </div>																																																																		
<p><b>CUSTOMER SERVICE INFORMATION CENTRE:</b> 1-800-361-5898, <a href="mailto:info@benjaminmoore.ca">info@benjaminmoore.ca</a>, <a href="http://www.benjaminmoore.ca">www.benjaminmoore.ca</a></p>																																																																		

◇ Reported values are for White. Contact Benjamin Moore for values of other bases or colours.

## ADVANCE® Waterborne Interior Alkyd Primer K790

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water-soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry.

**Difficult Substrates:** If the surfaces to be painted exhibit severe tannin or smoke staining, a Benjamin Moore solvent-based alkyd primer may be your best choice for conquering these severe conditions. Consult your Benjamin Moore retailer for further guidance.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions\\_questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions_questions_posees-eng.php)

### Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results use Benjamin Moore® ADVANCE® Waterborne Interior Alkyd Primer (K790) tinted to the approximate finish coat colour. **Special Note:** Certain custom colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your Benjamin Moore retailer.

#### Wood and engineered wood products

**Primer:** ADVANCE® Waterborne Interior Alkyd Primer (K790), Fresh Start® Multi-Purpose Latex Primer (F023), Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® All-Purpose Oil Based Primer (F024).

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

**Cabinetry**-All surfaces to be roughened by sanding (220 grit or coarser) before priming; light sanding between coats allows for a smoother finish; all dust must be cleaned.

#### Wood, MDF & Thermofoil

**Primer:** 1 coat ADVANCE® Waterborne Interior Alkyd Primer (K790)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish

#### Laminate (Formica)

**Primer:** 1 coat Fresh Start® High-Hiding All Purpose Primer (K046)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish

#### Plastic (Vinyl) veneer

**Primer:** 1 coat of ADVANCE® Waterborne Interior Alkyd Primer (K790) after removing plastic veneer by sanding away (an electric sander with a 100 grit paper works fine; manual sanding may need to be vigorous)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish

#### Drywall

**Primer:** ADVANCE® Waterborne Interior Alkyd Primer (K790).

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

#### Plaster

**Primer:** Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Latex Primer (F023)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

#### Rough or Pitted Masonry

**Primer:** Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

#### Smooth Poured or Pre-cast Concrete

**Primer:** Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Latex Primer (F023)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

#### Ferrous Metal (Steel and Iron)

**Primer:** Ultra Spec HP® Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish.

**Non-Ferrous Metal (Galvanized & Aluminum)** All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

**Primer:** Ultra Spec HP® Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

**Finish:** 1 or 2 coats of the appropriate ADVANCE® Waterborne Interior Alkyd finish

#### Hard Glossy Alkyd Surfaces:

Abrasion by sanding required for optimum adhesion.

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

### Application

Stir thoroughly before and during use. Apply one or two coats.

**Paint Application:** For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® Microfibre roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

**Spray, Airless:** Fluid Pressure: 1,500 – 2,500 psi  
Tip: 0.013 – 0.017

Extra ventilation is necessary under humid conditions to speed the dry time of ADVANCE®, especially when the paint is applied over sealed, hard, non-porous surfaces. The chart below is for general guidance.

Mild conditions	Severe conditions	Very severe conditions
Dry (RH < 50%), and temperature between 21 °C (70 °F) and 32 °C (90 °F)	(RH > 50%), and/or temperature between 10 °C (50 °F) and 21 °C (70 °F)	RH > 85%, or temperature <10 °C (50 °F)
ADVANCE® will dry normally. Dry to touch: 4-6 hours To Recoat: 8 hours	ADVANCE® will dry slower than normal unless the following is done to speed the dry time: <b>Ventilate the room with a fan and/or turn on A/C to lower the humidity.</b>	Do not apply ADVANCE®.

### Thinning/Clean up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Clean up with warm soapy water. Brushes and rollers should be given a final rinse with mineral spirits to remove residual alkyd. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

### Environmental Health & Safety Information

**Use only in a well ventilated area.** Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information.**

Benjamin Moore & Co., Ltd. 8775 Keele St., Concord, ON L4K 2N1 1-800-361-5898 [www.benjaminmoore.ca](http://www.benjaminmoore.ca) M72 K790 CE 031317  
ADVANCE, Benjamin Moore, Fresh Start, Gennex, Green Promise, Super Spec HP, Ultra Spec, Ultra Spec HP, and the triangle "M" symbol are registered trademarks of Benjamin Moore & Co., Ltd. All other marks are the property of their respective owner. This product is not endorsed by or a division of CHPS. This product is provided by Benjamin Moore, not CHPS. ©2010, 2017 Benjamin Moore & Co., Ltd. All rights Reserved