



REMOVE FINISH REMOVER 315

Features

- Removes both latex and oil finishes
- Fast-acting formula
- Removes clear finishes through solid color stains
- Concentrated formula

General Description

This product is designed for the removal of peeling oil or latex stain, varnish, and clear-coat wood finishes. It will also remove damaged and discolored wood fiber from all exterior wood surfaces: decking, siding, shingles and furniture. Restores wood to its natural tone and prepares the surface for recoating.

Recommended For

Residential or commercial applications. Previously finished, exterior wood surfaces.

Limitations

- Do not apply when air and surface temperatures are below 50°F (10°C)
- Remove, Finish Remover may darken certain wood types during application. If desired, use Brighten, Brightener & Neutralizer (317) to restore wood color back to its natural appearance.

Product Information

Colors — Standard: Not applicable	Technical Data N/A
—Tint Bases: Not applicable	Max Mixing Ratio (4:1) Mix 1 gallon of REMOVE with 4 gallons of water
— Special Colors: Not applicable	Coverage per Gallon Undiluted 100 - 200 Sq. Ft. Diluted (Max 4 Gallon water) 500 – 1000 Sq. Ft.
Certification VOC compliant in all regulated areas Very low in VOC's	Depending on dilution and surface conditions <hr/> Flash Point None <hr/> Surface Temperature – Min. 50°F – Max 90°F <hr/> Thin With Clean Water <hr/> Clean Up Thinner Clean Water <hr/> Weight Per Gallon 9.1 lbs <hr/> Storage Temperature – Min. 40°F – Max 90°F
Technical Assistance: Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com , or consult your local Yellow Pages.	Volatile Organic Compounds (VOC) <div style="text-align: center;">Exempt</div>

Remove, Finish Remover 315

Surface Preparation

Project surfaces may be damp or dry. Do not apply if surface temperature is below 50°F (10°C). Protect adjacent surfaces; cover with plastic and/or tape off any areas not being stripped. Pre-wet and/or cover vegetation; rinsing residue will not harm plants or roots. Exposure to concentrate may burn foliage.

It is recommended that you test product performance in an inconspicuous area prior to use.

PRIOR TO APPLICATION: Determine proper dilution following the chart below. Test a small, inconspicuous area and allow to dry before general use. Before and after application, liberally spray surrounding plants and vegetation with water. Avoid contact with metal, lawn furniture and fabric. If necessary, protect adjacent surfaces with plastic.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

MIXING: Remove, Finish Remover is a concentrate. This container makes up to 5 gallons of product.

Multiple Coats / Solid Color or Semi Solid Stain	Do not dilute
Weathered / Solid Color or Semi Solid Stain	Mix 1 gallon of REMOVE with 1 gallon of water
Semi Transparent Stain	Mix 1 gallon of REMOVE with 2 gallon of water
Transparent Stain	Mix 1 gallon of REMOVE with 3 gallon of water
Clear Finish	Mix 1 gallon of REMOVE with 4 gallon of water

DO NOT MIX CLEANER IN METAL CONTAINERS. NEVER MIX OR USE WITH OTHER CLEANERS OR CHEMICALS.

1. Apply product liberally to surface with plastic garden sprayer, brush or roller.
2. Allow solution to stand for 10-30 minutes, depending on age and type of finish to be removed.
3. Agitate with stiff bristle brush in direction of wood grain and rinse using a garden hose with nozzle or power washer.
4. Neutralize surface with Brighten, Brightener & Neutralizer (317) following label directions.
5. Allow to dry thoroughly. **Note:** When applying to vertical surfaces, apply from bottom to top.

CAUTION: Project surfaces will be extremely slippery.

CAUTION: This product is caustic. Wear goggles and rubber gloves when using this product.

Mixing

Mix according to the instructions above.

CLEAN UP: Clean equipment with warm, soapy water.

DISPOSAL: USE COMPLETELY OR DISPOSE OF PROPERLY. Local disposal requirements vary; consult your sanitation department or state designated environmental agency on disposal options.

Environmental, Health & Safety Information

Contains: Sodium Hydroxide and Sodium Metasilicate

CORROSIVE. CAUSES SEVERE BURNS TO EYES AND SKIN. MAY BE FATAL IF SWALLOWED. Contact with eyes may cause severe burns with possible corneal damage and blindness. Contact with skin may cause chemical burns or dermatitis. Vapors and mist may cause irritation to eyes and respiratory tract. Ingestion may cause gastrointestinal corrosion, vomiting, diarrhea, shock or death.

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection or face shield. Wear butyl gloves, impervious apron, boots and other clothing if needed to prevent contact. If spraying (only outdoors), use a NIOSH approved respirator. If you experience eye watering, headaches or dizziness, increase fresh air or wear a properly fitted vapor/particulate NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for use. **DO NOT MIX OR USE** with other household cleaners or chemicals. Close container after each use. Wash thoroughly with soap and water after each use. Exercise caution when working on surfaces that are wet, especially from cleaner. Wet surfaces are extremely slippery.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, immediately flush with water for 30 minutes while lifting upper and lower lids. In case of skin contact, wash with soap and water immediately, remove contaminated clothing and launder before reuse. If affected by inhalation of vapors or spray mist, remove to fresh air. If ingested and victim is conscious, give one glass of water or milk to dilute. **DO NOT INDUCE VOMITING.** Never give anything by mouth to an unconscious or convulsing victim. In all cases of exposure, call a physician immediately.

SPILL - Absorb with inert material and dispose of as specified under "DISPOSAL".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for
additional health and safety information.**