

Rotopax Mount Installation

Tools Required:

- 1/2" socket and ratchet

If Installing Rivnuts:

- 1/4" impact drill (recommended)
- 9/16" wrench
- 7/16" drill bit and drill

(The two rivnuts not on tabs should be used if double stacking Rotopax, using a Rotopax over 3 Gallons, or if severe terrain is common.)

Step 1: Attach the Rotopax Twist Mount to our Rotopax Mount as seen in the picture to the right.



Step 2: Attach the Rotopax and determine which position in the bed you would like to use. Remove the Rotopax once you have determined the location you'd like the mount. There are 4 different locations in the bed: front left, front right, left rear, and right rear.



Step 3: Remove the 2 plugs at whichever position you have decided to use.



Step 4: If you're not installing the additional rivnuts, skip to the **Step 6**. If you are installing the additional rivnuts, [here is a short video to explain how to use the rivnut tool](#). First you will need to drill the 2 holes. Line up the mount with the existing bed holes and mark where you will need to drill. Use a 7/16" drill bit to drill your 2 holes.

Step 5: With the holes drilled you can insert the rivnut and assembly tool into the hole and tighten it up using a 9/16" wrench and a 1/2" socket (recommended with an impact drill). Back the tool out and move to the next one.

Step 6: Loosely thread in the 2 tabs using the supplied 1/2" hardware as seen to the right.



Step 7: Position the tabs so that the long side will slide into each of the holes first. It **IS** a tight fit, but it helps the mount be very rigid with the bed side. Once they are in, tighten with the 1/2" socket. If additional rivnuts were used, install that hardware as well.