

REAR UFO INSTALLATION INSTRUCTIONS



PARTS LIST	QTY
UFO, Billet Aluminum	2
Rubber Expansion Nuts, 1/4"-20	2
SS 1/4"-20 x 1" Flat Head Socket Screw	2

REQUIRED TOOLS

5/32" Hex L-Key

PLEASE READ BEFORE BEGINNING INSTALLATION


Prior to starting the installation of this product we suggest reading the entire instruction manual. Several of the steps involved in installation of this product are fairly complex and reading through ahead of time will help you with a pain free installation. An extra minute or two spent now will save a lot of headache down the road.

This product must be installed by someone with a certain amount of mechanical aptitude. Vector OffRoad can not be held liable for damage caused to your vehicle due to poor or incomplete installation of this product. If you have any questions, are missing parts or need help locating a skilled installation shop in your area please contact us.

UFO's are for added cosmetic appearance and do not add to the functionality of the vehicle. They are not to be used where a factory rear tire carrier is still in service as they replace the factory tire carrier rubber bumper support pieces.



- 1. Remove the two OEM tire carrier rubber bumper pieces by pulling away from the vehicle and twisting counter clock wise. You should not need any tools to remove this piece.
- 2. Pre-assemble the rear UFO's by inserting the flat head bolt through the UFO and threading the rubber expansion nut onto the backside. Tighten the rubber expansion nut by hand until it is touching the backside of the UFO. DO NOT put the rubber expansion nut into the hole with out the UFO attached as it may fall into the tailgate of the vehicle.
- 3. Place the assembly into the hole and hold it flush to the surface of the tail gate. Hand tighten the flat head socket screw using a 5/32" Hex L-Key or similar tool. As the screw is tightened the rubber expansion nut will expand filling the hole.



COMMENTS OR QUESTIONS PLEASE CONTACT:

VECTOR OFF ROAD

PHONE: 801-372-7834 or 951-691-7604

EMAIL: admin@vectoroffroad.com

WEBSITE: http://www.vectoroffroad.com