

CL-600 LAMINATOR



CL-600 Laminator provides you definite durability and security on a card printed by DNP CX-printer! There is no doubt it is now essential for any ID card everywhere, such as governmental application, corporate & student ID, and even for several membership cards.

Product Lineup

DNP Generic Hologram Overlay

1,000 images/roll

Clear 1.0 or 0.6mil Patch

600 images/roll

Clear 1.0 or 0.6mil Patch with IC chip cut

600 images/roll

***various customization is available**

1.0/0.6mil patch is the best solution to give total durability against abrasion, water & humidity, and UV light that may damage the printed image, and it makes you get away from fading concern.

Hologram Overlay has almost same durability against water & humidity and UV light as patch. And above all, it can make your printed card unique and secure that prevents any counterfeiting by third parties.

Product Specifications

Dimensions : 210mm(W) x 333mm(D) x 360mm(H)

Weight : CL-600S/ Single side : less than 6.5kg

CL-600D/ Dual side : less than 8.0kg

Power dissipation : Maximum 3A (100 to 120V)

Maximum 1.5A (220 to 240V)



CX-D80 + CL-600

Basic Specifications

Laminating Method : Thermal roller transfer

Laminating side : Single sided(CL-600S), Double sided(CL-600D)

Laminating Speed : 16 – 36 sec per card: single and double sided

Connection : Infrared communication with CX-D80

Temperature config : 90°C - 180°C(adjustable on 5°C basis)

Speed config : 3 mm/s – 12 mm/s (adjustable on 0.5mm/s basis)

Laminating Media : 1.0/0.6 mil patch, 1.0/0.6 mil smart card patch, overlay foil
(Clear or Holographic selectable for all the media)

Safety Regulations : UL, EN60950-1, VCCI-B, FCC Class B, EN Class B, RoHS, CCC

