

Manufactured by URBAN RESTORATION GROUP PTY LTD Tel: 818 247 2555
1146 N Central Ave. # 531 Fax: 818 247 2515
Glendale CA 91202

HERITAGE GRAFFITI REMOVER

MATERIAL SAFETY DATA SHEET

IDENTIFICATION

Heritage Graffiti Remover

OTHER NAMES: Bare Brick Stone & Masonry Graffiti Remover Cool For Schools

UN Number: None allocated
Class: None allocated
D.G.Class: Non D.G.
Packaging Group: None allocated
Hazchem Code: None allocated
Poison Schedule: Not scheduled

HAZARDOUS BY DEFINITION OF OSHA'S HAZARDOUS COMMUNICATION STANDARD 29 CFR 1910.1200

USE: A unique Product blended specifically for the removal of spraycan type paints and other markers from brickwork, stonework and masonry on old buildings. Generally used for the removal of spraycan paint (graffiti) from unpainted brick, stone and masonry surfaces. Mainly intended for use in outside situations. Suitable for application by brush.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Red brown liquid

FLAMMABILITY LIMITS (%): Not Assigned

VAPOR PRESSURE: 39mm Hg at 66.2°F (19°C)

FLASH POINT: >147.2°F (>64°C) Closed Cup

SPECIFIC GRAVITY: 0.95+/-0.01 at 68°F (20°C)

BOILING POINT: 392°F (200°C)

SOLUBILITY IN WATER: Emulsifiable

PH: 13.5

INGREDIENTS

Proprietary

Natural Citrus Oils

Surfactant

Ethyl Alcohol

Alkaline Salts

CAS Number

5989-27-6

9016-45-9

64-17-5

1310-58-3

Proportion

10-30%

10-60%

0-10%

10-60%

0-5%

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

Flammability: 1

Health : 2

Reactivity: 0

Manufactured by URBAN RESTORATION GROUP PTY LTD Tel: 818 247 2555
1146 N Central Ave. # 531 Fax: 818 247 2515
Glendale CA 91202

HERITAGE GRAFFITI REMOVER

HEALTH HAZARD INFORMATION

INGESTION: Severely irritating. Ingestion will cause damage to the respiratory tract.

EYE: Severely irritating. Contact may cause redness, pain and blurring of vision. Corneal injury and burns may result unless removed promptly.

SKIN: Irritating. Contact with the product may defat the skin and contribute to dermatitis. This product may be absorbed through intact skin.

INHALATION: Product is intended for use outdoors however in extremely confined situations Vapor may be irritating to the eyes. Prolonged inhalation may cause drowsiness.

ADVICE TO DOCTOR: Treat symptomatically.

FIRST AID PROCEDURES

INGESTION: Never give an unconscious person anything to drink nor attempt to induce vomiting. If swallowed DO NOT induce vomiting, give water and seek URGENT medical attention.

EYE: Immediately hold eyelids open and rinse the eye continuously with a gentle stream of clean running water for at least five minutes. Seek medical advice immediately.

SKIN: Remove contaminated clothing and wash thoroughly with soap and water. Use water alone, if soap is unavailable. Apply a moisturizing hand cream, if available. Seek medical attention if any soreness or inflammation of the skin persists.

INHALATION: Remove affected person to fresh air and URGENTLY seek medical advice. Apply artificial respiration if breathing has stopped.

ADVICE TO DOCTOR: Treat symptomatically.

PRECAUTIONS FOR USE

EXPOSURE LIMITS: Ethyl Alcohol (64-17-5) 1000 ppm 1880mg/m³

VENTILATION: Use only outdoors in well ventilated conditions.

Manufactured by URBAN RESTORATION GROUP PTY LTD Tel: 818 247 2555
1146 N Central Ave. # 531 Fax: 818 247 2515
Glendale CA 91202

HERITAGE GRAFFITI REMOVER

PERSONAL PROTECTION: Always wear chemical resistant safety goggles, gloves or gauntlets and overalls when using this product.

FLAMMABILITY: Combustible. Avoid heat any sources of ignition.

INCOMPATIBILITY: Strong oxidizing agents and acids.

SAFE HANDLING PROCEDURES

STORAGE AND HANDLING

Store in a designated no-smoking area away from all sources of ignition, out of direct sunlight in a cool well ventilated area. Keep separate from oxidizing materials. Empty containers can possibly be hazardous when empty as they may contain vapor or product residues. Do not store with foodstuffs etc. Keep containers closed when not in use.

SPILLS & DISPOSAL:

SPILLS: Ensure that there are no sources of ignition present. Remove unnecessary people from the affected area. Wear protective equipment as specified for handling. If possible dam the spill. Cover with absorbent such as earth, sand or a commercial oil absorber. Sweep up and collect. Place in drums and dispose of to an approved facility for chemical waste. The residue may be washed away with water; however do not let product enter drains, sewers or watercourses.

DISPOSAL: If possible return product to supplier. Otherwise dispose by controlled incineration or to approved landfill. Comply with all local, state and federal regulations.

FIRE EXPLOSION: At above flash point, vapors can form explosive mixtures with air within flammable limits noted above. Vapor is heavier than air and can flow along the ground making distant ignition possible. Contact with strong oxidizers may cause fire. May be sensitive to static discharge.

EXTINGUISHING MEDIA: Extinguish using dry chemical foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool. If a fire occurs wear full protective clothing and NIOSH approved self-contained breathing apparatus with a full face. Operate in the pressure demand or other positive pressure mode.

HAZARDOUS DECOMPOSITION PRODUCTS: This product is stable under ordinary conditions of use and storage. Carbon monoxide and unidentified organic components can be formed during fire involvement.

Manufactured by URBAN RESTORATION GROUP PTY LTD Tel: 818 247 2555
1146 N Central Ave. # 531 Fax: 818 247 2515
Glendale CA 91202

HERITAGE GRAFFITI REMOVER

REGULATORY INFORMATION

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65)

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to the proposition.

CONTACT POINT

Customer Service: 818 247 2555