



KELLER HEARTT OIL
4411 SOUTH TRIPP AVE
CHICAGO, IL 60632
(773)247-7606

Technical Data Sheet

TRUEGARD K1- KEROSENE

General Information

TRUEGARD KEROSENE (K-1) is a near colorless special low sulfur refined petroleum distillate suitable for use in kerosene burner applications. It has a mild characteristic petroleum odor.

Toxicity

Prolonged and/or repeated inhalation of vapors may cause damage to the central nervous system and prolonged and repeated skin contact will cause irritation. Contact with the eyes will cause immediate irritation. Ingestion may be lethal.

Shipping and Handling

Kerosene is a flammable hydrocarbon liquid. Keep away from ignition sources. Keep containers closed and clearly labeled. Tank cars and trucks should bear D.O.T. placards that comply with all regulations. The UN number for Kerosene is UN-1223.

Ultra-Clear K-1 Kerosene Properties and General Specifications

Physical Properties	Test Method	Results	K-1 Specs
Sulfur Content	D-4294	.0396	.040
Gravity, API	D-287	46.1	
Doctor Test	D-4952	Neg.	
Copper Corrosion	D-130	2	3
Flash Point, F	D-93	112	100 min
Color	D-156	+26	+16
Distillation, F	D-86		
10% volume recovered, max		330	400
Final boiling point, max		470	572
Specific Gravity		.795	
WT (ppg)		6.622	