

TECHNICAL DATA SHEET

RUST VETO® 4214

SOLVENT-BASED RUST PREVENTIVE

RUST VETO® 4214 is a rust preventive that is exceptionally stable in wet conditions, particularly where there is alkaline, acid or solvent emulsion rinse water left on parts. It offers prolonged effectiveness where rinsing is not always thorough.

RUST VETO® 4214 releases displaced water within minutes and leaves a very thin, transparent protective film.

Up to 12 months indoor corrosion protection leaving a dry-to-touch film. FORD TOX 3347, Rolls Royce CSS 122B, Honda and GM approvals.

Applications

Dip, spray or brush application.

Recommendation For Use

Product is used neat.

Benefits

- Easy to apply - displaces and separates water quickly
- Exceptional stability - even in acid or alkaline conditions
- Excellent humidity protection
- Easily removed with a mild alkaline cleaner or petroleum solvent
- Compatible with all metals

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Typical Physical Properties

PROPERTY	TYPICAL VALUE	UNIT
Flash Point	108°F	PMCC
Viscosity @ 100°F	32	SUS
Film Thickness	0.1	mil
Coverage	1900	sq ft / gal
Dry to Set Time	1 - 2	hours
ASTM D-1748	Passes 30+ days (typical)	Humidity at 120° F

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 21421400

