



PA-4040

Order No.: 17.2520

EUR 899,00

RRP*

PRODUCTINFOS

4-zone matrix mixing amplifier,

with professional features for general multi-room PA applications.

- 40 W per zone
- 100 V and 4/8 Ω operation
- Perfect utilisation of the capacity and reliable protection of connected speakers due to an integrated limiter
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control, channel mute switch and routing switch for zones
- Microphone inputs with +15 V phantom power, can be activated as required
- Priority function for channel 1, switchable
- Independent paging input, can be routed to all zones
- 4 zone outputs, can be controlled individually
- Zone and monitor line outputs for additional amplifiers or recorders
- Connection for monitor speakers
- Level control via VU meters for zone and monitor



- · Adjustable headphone output
- Temperature-controlled fan, continuously adjustable
- 230 V mains operation

PROSOUND 02/2008

"You have to practice a very long time in order to cause an operating error. An absolutely useful unit available at a favourable price."

TECHNICAL SPECIFICATIONS

PA-4040

Channels 5 Zones 4

Power rating $4 \times 40 \text{ W}$ Peak music power output (P_{MAX}) $4 \times 65 \text{ W}$

5 mV/4 k Ω , 100 mV/10 k Ω (mic/line),

Inputs $100 \text{ mV/30 k}\Omega \text{ (line)}$

Frequency range 50-17,000 Hz

Integrated limiter yes

Equalizer bass \pm 10 dB/100 Hz Equalizer treble \pm 10 dB/10 kHz

S/N ratio > 65 dB (mic), > 75 dB (line)

THD < 1%

Power supply $\sim 230 \text{ V/}50 \text{ Hz/}450 \text{ VA}$

 $\begin{tabular}{lll} Mains voltage & $\sim 230 \ V$ \\ Mains frequency & 50 \ Hz \\ Power consumption, operation & 450 \ VA \\ Admiss. ambient temp. & 0-40 \ ^{\circ}C \\ \end{tabular}$

Dimensions 482 x 133 x 310 mm, 3 RS

Width 482 mm
Height 133 mm
Depth 310 mm

Rack spaces, RS 3
Weight 15 kg



PA-4040

Connections

3 x combo 6.3 mm/XLR (mic/line),

2 x RCA L/R (line),

screw terminal (speaker zone),

screw terminal (speaker monitor),

screw terminal (mix out),

screw terminal (paging),

screw terminal (priority)

3.5 mm stereo jack (headphones)

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.