



## PA-948

Order No.: 17.5070

**Price upon request**

### PRODUCTINFOS

#### Mono PA mixing amplifier

- 1 x 480 W
- 4 balanced microphone inputs and line inputs with selectable priority
- 4 stereo line inputs
- Speaker outputs via screw terminals
- Balanced line output
- Record output
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- 2-tone or 4-tone chime, can be activated externally
- Input level control and output level control
- 2-way tone control for the output
- Switchable 48 V phantom power for microphone inputs
- Temperature-controlled fan
- Mains operation or 24 V emergency power operation
- Removable mounting brackets

### TECHNICAL SPECIFICATIONS

**PA-948**

Channels	5
Power rating	480 W
Peak music power output ( $P_{MAX}$ )	680 W
Inputs	2.5-100 mV (mic), 350 mV (line)
Frequency range	50-16,000 Hz, $\pm 3$ dB
Equalizer bass	$\pm 10$ dB/100 Hz
Equalizer treble	$\pm 10$ dB/10 kHz
S/N ratio	> 75 dB
THD	< 0.1%
Power supply	$\sim 230$ V/50 Hz/1,090 VA, DC 24 V/27 A
Mains voltage	$\sim 230$ V
Mains frequency	50 Hz
Power consumption, operation	1,090 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 27 A
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 137 x 395 mm, 3 RS
Width	482 mm
Height	137 mm
Depth	395 mm
Rack spaces, RS	3
Weight	19 kg
Connections	4 x XLR (mic), 4 x RCA L/R (line), 1 x XLR (line out), 1 x RCA L/R (line out), screw terminals (speakers)