



EDL-36TW

Order No.: 16.2070

EUR 77,90

RRP *

PRODUCTINFOS

PA ceiling speaker,

for a high safety level in case of a fire.

- 100 V line technique
- Additional integrated tweeter
- Fire protection cover
- Metal housing with fitted ceramic terminal
- Thermal fuse: 1 A/150 °C, for disconnecting a faulty speaker in case of a short circuit (fire), so that the function of one speaker line is maintained
- 3-step power selector switch
- Earth connection
- Glass fibre insulated supply line with high-strength cable gland
- Quick-mounting facility
- For a ceiling thickness from 2 to 40 mm

TECHNICAL SPECIFICATIONS

EDL-36TW

Line technique	100 V
Frequency range	150-20,000 Hz
Power rating	10/5/2.5 W
Mounting cutout	Ø 190 mm
Mounting depth	90 mm
Dimensions	Ø 200 mm x 100 mm
Outside diameter	Ø 200 mm
Width	Ø 200 mm
Depth	100 mm
Weight	1.5 kg
Sales unit	1
Type of speaker	165

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.