



PA-900

Order No.: 17.1190

EUR 425,00

RRP *

PRODUCTINFOS

Mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- 4 balanced mic/line inputs
- Mic 1 with priority circuit and automatic talkover
- Additional connection for desktop microphone via screw terminal
- 1 aux input
- Speaker outputs via screw terminals
- Line output
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- Input and output level controls
- 2-way tone control for the output
- 20 V phantom power for each microphone input, can be selected individually
- Mains operation or 24 V emergency power operation
- Removable mounting brackets

TECHNICAL SPECIFICATIONS

PA-900

Channels	5
Power rating	120 W
Power rating at 4 Ω	120 W
Power rating at 100 V	120 W
Peak music power output (P_{MAX})	160 W
Output impedance	4 Ω
Inputs	3 mV (mic), 200 mV (line), 140 mV (aux)
Frequency range	50-15,000 Hz, ± 3 dB
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 80 dB
THD	< 0.5%
Power supply	~ 230 V/50 Hz/300 VA, DC 24 V/9 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	300 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 9 A
Admiss. ambient temp.	0-40 $^{\circ}$ C
Dimensions	482 x 88 x 275 mm, 2 RS
Width	482 mm
Height	88 mm
Depth	275 mm
Rack spaces, RS	2
Weight	9.9 kg
Connections	4 x XLR (mic/line), 1 x RCA L/R (aux), screw terminals (speakers)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.