



DIB-100

Order No.: 24.1140

EUR 37,90

RRP *

PRODUCTINFOS

DI Boxes

For an optimum signal transmission from musical instruments to a mixer or amplifier. By using a transformer coupling, interferences due to matching problems, e.g. hum loops, are prevented to a large extent. Input and output are galvanically isolated.

For adapting line levels, please use units of the LTR series!

DI box

- 3-fold attenuation switch (0/-20/-40 dB)
- Ground lift switch
- Instrument feed-through output
- Wideband balancing transformer
- Robust metal housing

PRODUCTION PARTNER 04/2013

"The measured values and workmanship give no reason for criticism. When considering the price, too, you can't go wrong."

TECHNICAL SPECIFICATIONS

DIB-100

Type	DI box
Frequency range	15-30,000 Hz, ± 0 dB
Input impedance	50 k Ω
Output impedance	600 Ω (bal.), 50 k Ω (unbal.)
Gain	0/-20/-40 dB
Transmission ratio	10:1
Admiss. ambient temp.	0-40 °C
Dimensions	74 x 45 x 130 mm
Weight	560 g
Inputs	6.3 mm jack, unbal 6.3 mm jack, unbal.,
Outputs	par. out XLR, bal.

DIB-100

Width	74 mm
Height	45 mm
Depth	130 mm

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.