



FGA-202

Order No.: 25.1660

EUR 77,90

RRP *

PRODUCTINFOS

Professional 2-channel line transformer,

for reducing signal interference and hum loops.

- 2 inputs via balanced comb. jacks XLR/6.3 mm (600 Ω)
- 2 galvanically isolated XLR outputs (600 Ω) with ground lift switch
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 650 g

SOUNDCHECK 07/2007

tools4music 06/2009

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

"Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price."

on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

"Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case."

TECHNICAL SPECIFICATIONS

FGA-202

Type	transformer
Frequency range	20-20,000 Hz
Input impedance	600 Ω
Output impedance	600 Ω
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 55 x 75 mm
Weight	650 g
Inputs	2 x comb. jack XLR/6.3 mm, bal.
Outputs	2 x XLR

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.