



PA-324

Order No.: 17.4420

EUR 629,00

RRP *

PRODUCTINFOS

Mono PA mixing amplifier

- 1 x 240 W
- 3 microphone inputs, one of which is a balanced input
- Mic 1 with priority circuit and adjustable automatic talkover
- 2 aux inputs
- 1 telephone input for telephone systems with audio output
- Speaker outputs via screw terminals
- 1 line output
- Input and output level controls
- 2-way tone control for the output
- 48 V phantom power for channel 1, can be activated as required
- 482 mm (19") rack installation with supplied mounting brackets

TECHNICAL SPECIFICATIONS

PA-324

| | |
|--------------|-------|
| Channels | 6 |
| Power rating | 240 W |

PA-324

| | |
|---------------------------------------|---|
| Peak music power output (P_{MAX}) | 340 W |
| Inputs | 5 mV/600 Ω (mic), 350 mV/10 k Ω (aux), 1 V/10 k Ω (telephone) |
| Frequency range | 50-16,000 Hz |
| Equalizer bass | \pm 10 dB/100 Hz |
| Equalizer treble | \pm 10 dB/10 kHz |
| S/N ratio | 66 dB (mic) 80 dB (aux) |
| THD | < 0.5% |
| Power supply | \sim 230 V/50 Hz/740 VA |
| Mains voltage | \sim 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 740 VA |
| Admiss. ambient temp. | 0-40 $^{\circ}$ C |
| Dimensions | 430 x 88 x 380 mm, 2 RS |
| Width | 430 mm |
| Height | 88 mm |
| Depth | 380 mm |
| Rack spaces, RS | 2 |
| Weight | 16.6 kg |
| Connections | 1 x 6.3 mm/XLR (combo), 1 x 6.3 mm jack (mic 1), 2 x 6.3 mm jack (mic 2-3), 2 x RCA L/R (aux 1-2), screw terminals (telephone), 1 x RCA L/R (line out) |

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.