



PA-4120

Order No.: 17.0810

EUR 1329,00

RRP *

PRODUCTINFOS

PA power amplifiers

- 4 x 240 W (PA-4240)
- 4 x 120 W (PA-4120)
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-4120

Channels	4
Power rating	480 W
Power rating at 4 Ω	4 x 120 W
Power rating at 100 V	4 x 120 W

PA-4120

Output impedance	22 V/4 Ω , 50 V/21 Ω , 70 V/41 Ω , 100 V/83 Ω
Inputs	1.2 V, bal.
Frequency range	55-17,000 Hz, -3 dB
S/N ratio	> 90 dBA
THD	< 1%
Power supply	~ 230 V/50 Hz/1,400 VA, DC 24 V/60 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 60 A
Admiss. ambient temp.	0-40 °C
Dimensions	483 x 133 x 370 mm, 3 RS
Width	483 mm
Height	133 mm
Depth	370 mm
Rack spaces, RS	3
Weight	25 kg
Connections	4 x XLR (inputs), screw terminals (speakers)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.