



PA-704

Order No.: 0179480

PRODUCTINFOS

Mono PA mixing amplifier

- 1 x 35 W
- Silent operation due to fanless cooling concept
- 2 low-impedance microphone inputs
- 1 aux input, 1 phono input
- Speaker outputs via screw terminals
- Input and output level controls
- 2-way tone control for the output
- Connection for a microphone talk button to switch off the other sources during announcements
- Mains operation and 12-24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-704

Peak output power	70 W
Power rating	35 W
Channels	4

PA-704

Inputs	5 mV (mic), 210 mV (aux), 5 mV (phono)
Frequency range	100-18,000 Hz
Equalizer bass	±10 dB/150 Hz
Equalizer treble	±10 dB/6 kHz
S/N ratio	> 55 dB
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	100 VA
Operating voltage (possible alternative)	DC 12-24 V
Power supply (possible alternative)	DC 2.5 A
Admiss. ambient temp.	0-40 °C
Width	320 mm
Height	85 mm
Depth	230 mm
Weight	4.97 kg
Connections	2 x 6.3 mm jack (mic), 1 x RCA L/R (aux), 1 x RCA L/R (phono), connecting terminals (speakers)