



PA-803DAP

Order No.: 1000168

PRODUCTINFOS

Mono class D PA mixing amplifier,

with integrated MP3 player, FM/DAB+ tuner and Bluetooth.

- 1 x 30 W
- Class D concept with high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- Bluetooth version 4.2
- MP3 player with USB/SD interface, FM/DAB+ radio, LED display, infrared remote control
- Reception of interference-free 'digital radio' (DAB+)
- 1 balanced XLR microphone input with 48 V phantom power and priority selection for announcements
- 2 unbalanced inputs, switchable mic/line
- 2 unbalanced line inputs
- 1 emergency input
- 1 Music-On-Hold output (MOH)
- Speaker outputs via screw terminals
- 2 line outputs
- Input level control and output level control
- 2-way tone control for the output
- LEDs for indicating operation, clipping, protect and signal level

TECHNICAL SPECIFICATIONS

PA-803DAP

| | |
|--|--|
| Power rating | 30 W |
| Channels | 1 |
| Zones | 1 |
| Inputs | 4.5 mV/600 Ω (mic 1-3), 120 mV (line 2-3), 60 mV (line 4-5) 90 mV (tel.) |
| Frequency range | 60-15,000 Hz |
| Equalizer bass | yes |
| Equalizer treble | yes |
| S/N ratio | 72 dB (mic) 85 dB (line) |
| THD | < 0.5% |
| Phantom power | 48 V |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 100 VA |
| Operating voltage (possible alternative) | DC 24 V |
| Power supply (possible alternative) | 2.5 A |
| Admiss. ambient temp. | 0-40 °C |
| Width | 320 mm |
| Height | 95 mm |
| Depth | 245 mm |
| Weight | 3.74 kg |
| Connections | 1 x XLR (mic 1), 2 x 6.3 mm jack (mic 2-3/line 1-2), 2 x RCA L/R (line 3-4), 2 x RCA (master out), 1 x IEC (FM), screw terminals (emergency, MOH, DC 24 V, speakers) |
| Packing dimensions (W x H x L) | 0.39 x 0.16 x 0.3 m |
| Gross weight | 4.33 kg |
| Net weight | 3.74 kg |