



STA-850D

Order No.: 25.2360

Price upon request

PRODUCTINFOS

8-channel class D amplifier

- Silent operation due to fanless cooling concept
- 8 Ω bridged operation possible
- Mute function for each channel
- 8 level controls
- 1 LED per channel for indicating overload (clip)
- Protected against short circuit

TECHNICAL SPECIFICATIONS

STA-850D

Channels	8
Power rating	400 W
Power rating at 4 Ω	8 x 50 W
Power rating at 8 Ω	8 x 30 W
Power rating with 8 Ω bridged operation	4 x 100 W
Peak music power output (P_{MAX})	600 W
Inputs	1 V/20 k Ω unbal. 550 mV/20 k Ω bal.

STA-850D

Frequency range	10-20,000 Hz
Crosstalk attenuation	> 45 dB
Power supply	~ 230 V/50 Hz/600 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	600 VA
Admiss. ambient temp.	0-40 °C
Dimensions	483 x 90 x 330 mm, 2 RS
Width	483 mm
Height	90 mm
Depth	330 mm
Rack spaces, RS	2
Weight	10.5 kg
Connections	8 x XLR, bal.
	8 x RCA
	8 x spring-load. speaker term. L/R