



## WALL-06T/SW

Order No.: 0163600

### PRODUCTINFOS

#### Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in black
- 4 power taps as well as switchable to 8 Ω operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

### TECHNICAL SPECIFICATIONS

#### WALL-06T/SW

Active/passive	passive
Transmission method	100 V
Total power rating	100 W
Power rating (RMS)	32/16/8/4 W (100 V) 50 W (8 Ω)

**WALL-06T/SW**

Impedance	8 $\Omega$
Frequency range	70-20,000 Hz
System	2-way
Bass speaker	16 cm (6") bass-midrange speaker
Tweeter	25 mm (1") dome tweeter
Number of speakers	2
Speaker size	6"
Sensitivity	90 dB/W/m
Max. rated SPL	106 dB
Housing material	plastic
Colour	black
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	0-40 °C
Dimensions	196 x 303 x 250 mm (with bracket)
Width	196 mm
Height	303 mm
Depth	250 mm
Weight	3.5 kg
Inputs	spring-load. speaker term.
Other features	for pivoting and tilting
Packing dimensions (W x H x L)	0.23 x 0.33 x 0.5 m
Gross weight	7.63 kg
Net weight	6.97 kg